

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7988)

-----  
A Fir tree 10" dia., which I mkd. T31S R6W S3 on NE.; S10 on SE.; S9 on SW.; and S4 on NW. faces, with 3 notches on E. and 5 notches on S. edges for the cor. to secs. 3, 4, 9 and 10, from which

- A Fir 16" dia., bears N.28°E., 9 lks. dist. mkd. T31S R6W S3 BT.
- A Fir 12" dia., bears S.80°E., 25 lks. dist. mkd. T31S R6W S10 BT.
- A Fir 18" dia., bears S.25°W., 15 lks. dist. mkd. T31S R6W S9 BT.
- A Fir 14" dia., bears N.45°W., 45 lks. dist. mkd. T31S R6W S4 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey, Clete Putnam, crew - May 23, 1960 - C.S. 52/25-2

-----  
Found - Fir now 24", alive and standing. Some bark scribing and notches still visible.  
Fir now 21", N.28°E., 6 ft. alive and standing, shows bark scribing "3S BT"  
Fir now 24", S.80°E., 16.5 ft. shows good scar. Do not open.  
Fir now 28", S.25°W., 10 ft. bark scribing still visible, "8S BT" and fragments of other scribing alive and standing.

No trace of NW bearing tree.

Set a Witness Corner to Sec. Cor., 4.3 ft. East of true corner. Set Iron pipe with brass cap mkd:

County Surveyors Office  
T 31 S R 6 W  
W.C. 4.3 ft. to cor.  
S 4 | S 3  
S 9 | S 10  
1960

Blaze and scribe:

16" R.Fir N.8°W., 48.0 ft. scribed T31S R6W WC S4 CS BT.

Cor. Fd. and Used in BLM survey by Jelley and Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records, Vol. 45 Page 17303)

Fd. OK by K. DeGroot, Jan. 2004 - M137-77