



TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. & used on BLM dependent resurvey by A. Bert Skeesick & Timothy Moore, Cadastral Surveyors under Group #1950, surveyed April/May 2000 (DCS0 rec. Vol. 53 Page"(s) 20667

Stephan Barott - 3/2011 - C.S. File 65/72-11  
-----  
Monument & BTs are in good condition but I did not tie them in.  
Geodetic Latitude - 42.511870406N  
Geodetic Longitude - 123.235004633W  
NAD83

Gregg Neitsch for Carbon River Holdings LLC - 12/2025 - M186-56  
-----  
Found - 1" diam. Galvanized iron pipe with a 2.5" diam. Brass cap stamped "T31S R6W 1/4 S22/S27 1964"  
Top of mon. is 14" above ground.  
30" D. Fir stump, rotted. S.84°E. 22.1 ft. by compass and tape.  
12" D. Fir with healed blaze. N.29°E. 13.4 ft. by compass and tape. (Rec. N.29°30'E.)  
12" D. Fir with healed blaze. N.48°W. 19.2 ft. by compass and tape. (Rec. N.48°30'W.)  
30" D. Fir stump. N.66°W. 35.5 ft. by compass and tape. (Rec. N.66°30'W. 30.0 ft.)  
8" cedar with healed blaze. S.76°W. 16.7 ft. by compass and tape. (Rec. S.75°45'W.)  
16" D. Fir stump with visible scribing. S.28°W. 16.4 ft. by compass and tape. (Rec. S.27°30'W.)  
10" rotted stump. North 19.5 ft. by compass and tape  
Notes - See M125-3 and Dependent BLM resurvey from April 19, 2002 for more information.