

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7987)

Set Fir post 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which

A Laurel 10" dia., bears N.10°W., 16 lks. dist. mkd. 1/4 S BT.

A Laurel 5" dia., bears S.12°W., 12 lks. dist. mkd. 1/4 S BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17300)

Point for the 1/4 sec. cor. at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 31 S R 6 W
1/4 $\frac{S \ 10}{S \ 15}$
1980

from which

A Fir 5" dia., bears N.5 1/2°E., 32 1/2 lks. dist. mkd. 1/4 S10 BT

A Fir 16" dia., bears S. 1/2°W., 86 1/2 lks. dist. mkd. 1/4 S15 BT

Fd. Ok by K. DeGroot, May 2004 - M146-5