

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7989)

-----  
Set Fir post, 3 ft. long, 3" sq., 16" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which  
A Fir 10" dia., bears S.45°E., 13 lks. mkd. 1/4 S BT  
A Yew 10" dia., bears N.54°W., 25 lks. mkd. 1/4 S BT

George Wenderoth - May 1960 - C.S. File 49/92-2

-----  
Found - Yew Stake.  
10" Fir S.45°E., 8.6 ft. rotten scribe marked.  
Scribe new trees:  
15" yew S.77°17'E., 47.3 ft.  
10" Yew N.55°38'E., 36.5 ft.

Douglas Co. Surveyors Office - John Powell, Frank Jones, Cliff Stone, crew - Oct. 1966 - C.S. File 54/31-40

-----  
Found - 10" Yew, now 10", N.55 1/2°E., 36.5 ft. scribe visible.  
No trace of SE bearing tree.

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 6 W  
1/4 S 3  
S 10  
1966

New BT - 16" D.Fir N.82°E., 65.0 ft. mkd. 1/4 S3 CS BT.  
No trees near in Section 10.  
This corner lies on edge of old skid road. Also 40 ft. West of draw, N-S.

Fd. OK, George Grubb, April 1982, M 91-75

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1875, surveyed May 1998 - July 1998 - (DCSO records Vol. 53 Page(s) 20573-4)

-----  
Beginning at the 1/4 sec. cor. of secs. 3 & 10, perpetuated by Wenderoth, in 1960, further perpetuated by Powell, from original evidence no longer in existence; monumented with an iron post, 1 1/2" diam., firmly set, projecting 12" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE

T 31 S R 6 W  
1/4 S S 3  
S 10  
1966

from which a bearing tree mkd. by Wenderoth  
continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A yew, 10" diam., bears N.55 $\frac{3}{4}$ °E., 55 lks., with no marks visible on open decayed blaze.  
and a bearing tree mkd. by Powell  
A fir, 29" diam., bears N.82 $\frac{3}{4}$ °E., 96 lks., with healed double blazes.  
and a new bearing tree  
A fir, 9" diam., bears S.32 $\frac{1}{2}$ °W., 52 lks., mkd. 1/4 S10 BT.  
Corner is located on the E. edge of an abandoned dirt road, 30 lks. wide, extending N.15°W. & S.20°E., & W., 0.65 chs. from a ravine, drains N. 10° W.

From this point, the Bureau of Land Management, Geodetic Control Station No. EC41275, at latitude 42°54'03.450"N., longitude 123°23'36.245"W., (NAD 1983 (91)), determined by the NAVSTAR Global Positioning System, bears N. 47°05'48"E., 24.325 chs. (mean bearing and sea level distance), monumented with an aluminum cap, firmly set flush with the ground, with top mkd. GPS EC41275 1998.

Kristian DeGroot - For: Silver Butte Timber Co. - May 2004 - M146-5

-----

Found - 1 $\frac{1}{4}$ " iron pipe by Powell in 1966, firmly set, projecting 12" above the ground with a 2 $\frac{1}{2}$ " brass cap (properly) stamped.  
From which a BT by Wenderoth in 1960:  
A 10" Yew bears N.55°45'E., 36.5 ft., with no marks visible on an open rotted blaze.  
And a BT by Powell in 1966:  
A 32" D.Fir bears N.82°45'E., 63.6 ft., with a healed blaze.  
And a BT by Seibold in 1998  
A root hole bears S.32°30'W., 34.3 ft., with an uprooted 10" D.Fir with a healed blaze alongside.

New - 14" Alder bears S.32°'E. 30.2 ft. scribed "1/4 S10 BT"  
5/8"x30" iron rod bears S.82°45'W., 30.00 ft.  
5/8"x30" iron rod bears N.31°45'W., 20.00 ft.