TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 3; & Sec. 34, T30-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7193)

Set quarter sec. post, from which
B.Oak 6" dia., bears South, 22 lks. dist.
Red Fir 7" dia., bears N.10°W., 29 lks.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - May 23, 1960 - C.S. File 52/25-3

Found - Fir snag, now 30", N.10°W., 19.1 ft. Opened and found good scribe mkd. "T".
No trace of other BT.
Set I. pipe with brass cap mkd: County Surveyors Office 1960
T30S R6W ¼ S 34 / S 3
Blaze and scribe new trees:
18" R.Fir N.89½°W., 20.0 ft. "¼ S34 CS BT".
11" Maple S.9°W., 51.0 ft. "¼ S3 CS BT".

Fd. OK, Aug. 1981, George Grubb, M 88-67

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1875, surveyed May 1998 - July 1998 - (DCSO records Vol. 53 Page(s) 20576)