

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 446300

PRIMARY CORNER DESCRIPTION Witness Point bet. Secs. 22 & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by A. Bert Skeesick & Timothy Moore,  
Cadastral Surveyors under Group #1950, surveyed April/May  
2000 (DCSO rec. Vol. 53 Page"(s) 20666

-----  
Point selected for a witness point bet. secs. 22 & 27.  
Set a stainless steel post, 28" long, 2½" dia., 24" in the  
ground, with brass cap mkd. WP

T 31 S R 6 W

S 22

S 27

2000

from which

A fir, 8" dia., bears S.27½°W., 101.8 ft., mkd. X BT.

A cedar, 7" dia., bears N.50¾°W., 10.3 ft., mkd. X BT.

Each new bearing tree has a 2½" X ¼" magnetic nail (MAG-NAIL)  
driven at the base on the right side-center, unless otherwise  
described in the corner description.