

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; 2 & 3, T32-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7947)

Set post cor. to secs. 2, 3, 34 and 35 on NE. slope, from which

- A Fir 30" dia., bears S.38°W., 58 lks. dist.
- A Fir 20" dia., bears N.54°W., 47 lks. dist.
- A Fir 4" dia., bears N.54°E., 43 lks. dist.
- A Fir 20" dia., bears S.41°E., 118 lks. dist.

Douglas Co. Surveyors Office - John Powell, Frank Jones, Cliff Stone, crew - Oct. 1966 - C.S. File 54/31-22

Found - Orig. 24" now 32" D.Fir S.41°E., 77.9 ft. shows good scar.

Orig. 30" D.Fir, now snag, S.38°W., 38.3 ft. scribe visible "2"

Orig. 20" now 34" D.Fir, N.54°W., 31.0 ft. opened for scribe.

No trace of NE BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 6 W

S 34 | S 35

S 3 | S 2

1966

New BTs -15" D.Fir N.28°W., 23.8 ft. mkd. T31S R6W S34 CSBT

24" D.Fir N.43°E., 30.5 ft. mkd. T31S R6W S35 CSBT

16" D.Fir S.25°W., 18.0 ft. mkd. T32S R6W S3 CS BT

Fd. OK by O. Frederick, Feb. 1985, M 90-67 & C.S. 63/11

Cor. Fd. and used in BLM resurvey by Mark Dixon and Henry Hartley, under Group #1337, surveyed July/Sept. 1989 (DCSO records, Vol. 48 Pages 18562-63)