

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7970)

Set Yew post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 26, 27, 34 and 35, mkd. T31S R6W S26 on NE.; T31S S35 on SE.; S34 on SW. and S27 on NW. faces, with 1 notch on S. and 2 notches on E. edges, from which

A Chinkapin 8" dia., bears N.88°E., 33 lks. dist. mkd. T31S R6W S26 BT.

A Fir 16" dia., bears S.30°E., 17 lks. dist., mkd. T31S R6W S35 BT.

A Fir 16" dia., bears S.65°W., 47 lks. dist., mkd. T31S R6W S34 BT.

A Fir 10" dia., bears N.66°W., 41 lks. dist., mkd. T31S R6W S27 BT.

Douglas Co. Surveyors Office - John Powell, Frank Jones, Cliff Stone, crew - Oct. 1966 - C.S. File 54/31-25

Found - Orig. 16" now 29" D.Fir S.30°E., 11.2 ft. faint bark scribe "T3".

Orig. 16" now 21" D.Fir S.65°W., 31.0 ft. shows good scar.

10" now 21" D.Fir N.66°W., 27.1 ft. shows good scar.
No trace of NE BT.

Set Brass cap at cor. mkd: County Surveyors Office

T	31	S	R	6	W
	S	27		S	26
	S	34		S	35
				1966	

Reblazed and rescribed:

29" D.Fir S.30°E., 11.2 ft. mkd. T31S R6W S35 CS BT.

New BT - 10" D.Fir N.39°E., 25.5 ft. mkd. T31S R6W S26 CS BT.