

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7972)

Set Chinkapin post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 22, 23, 26 and 27, mkd. T31S R6W S23 on NE.; S26 on SE., S27 on SW.; and S22 on NW. faces, with 2 notches on E. and S. edges, from which

- A Laurel 8" dia., bears N.52°E., 25 lks. dist., mkd. T31S R6W S23 BT.
- A Laurel 10" dia., bears S.20°E., 31 lks. dist., mkd. T31S R6W S26 BT.
- A Laurel 8" dia., bears S.80°W., 22 lks. dist., mkd. T31S R6W S27 BT.
- A Laurel 8" dia., bears N.60°W., 55 lks. dist., mkd. T31S R6W S22 BT.

J.W. Cole - For: J.E. Reeves - Feb. 11-16, 1924 - Vol. 3 Pg. 181; Field Book 52 Pgs. 40-45; (and "old" corner book, page 163)

I renewed this corner from the original bearing trees. Set 1" x 40" drill steel for the corner and marked new trees as follows:

- A Fir 20" dia., S.76°30'W., 77.8 ft.
- A Fir 40" dia., N.45°15'W., 58.0 ft.
- A Fir 18" dia., N.59°45'W., 68.5 ft.

Douglas Co. Surveyors Office - John Powell, Frank Jones, Cliff Stone, crew - Oct. 1966 - C.S. File 54/31-26

Found - 1" steel drill at corner.

- Orig. 8" now 17" Laurel N.52°E., 16.5 ft. shows old scar but rotten.
- Orig. 10" now 13" Laurel S.20°E., 20.5 ft. opened scribe visible R6W S26.
- Orig. 8" now 12" Laurel N.60°W., 36.3 ft. shows old scar.
- 20" D.Fir now 22" S.76½°W., 77.8 ft.
- 40" D.Fir now 40", N.45°W., 58.0 ft.
- 18" D.Fir now 18", N.59½°W., 68.5 ft. (find this bearing to be N.59½°E.)

Trees have been blazed but no scribing present. Set Brass cap at cor. mkd: County Surveyors Office

T 31	S R 6W
S 22	S 23
S 27	S 26
1966	

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs -24" D.Fir S.3°E., 24.5 ft. scribed T31S R6W S26 CSBT
4" D.Fir S.53°W., 14.6 ft. scribed S27 CS BT.
10" D.Fir N.20°W., 15.3 ft. scribed T31S R6W S22 CS
BT.

Reblazed and Rescribed:
17" Laurel N.52°E., 16.5 ft. mkd. T31S R6W S23 CSBT

Fd. OK, Glenn Baughman, March 1984, M 96-32

BLM survey by Jelley and Rogers, under Group #1042, surveyed
Oct. 1980-Oct. 1981 (DCSO records, Vol. 45 Pages 17292-93)

The cor. of secs. 22, 23, 26, & 27, perpetuated by Cole, in
1924 and. by Powell, in 1966, monumented with an iron bar, 1"
square, firmly set, projecting 8" above ground, with an iron
post, 1¼" dia., firmly set alongside, projecting 13" above
ground, with brass cap (properly) mkd.
from which the remaining original bearing trees

A madrone, 17" dia., bears N.52°E., 25 lks., with
illegible scribe marks visible on partially healed
blaze.

A madrone, 12" dia., bears S.20°E., 28 lks., with
illegible scribe marks visible on partially healed
blaze. (Record 31 lks.)

A madrone, 8" dia., bears N.60°W., 55 lks. with healed
blaze.

and bearing trees marked by Cole in 1924

A fir, 28" dia. bears S.76½°W., 118 lks. with healed
blaze.

A fir 40" dia. bears N.45°W., 88 lks., with healed blaze.

A fir, 18" diam., bears N.59½°W., 104 lks., with healed
blaze.

and bearing trees marked by Powell in 1966

A fir, 28" dia. bears S.3°E., 37 lks., with healed blaze.

A fir, 6" dia., bears S.53°W., 22 lks. dist. with healed
blaze.

A fir, 11" dia., bears N.20°W., 23 lks. with healed blaze.

BLM dependent resurvey by A. Bert Skeesick & Timothy Moore,
Cadastral Surveyors under Group #1950, surveyed April/May
2000 (DCSO rec. Vol. 53 Page"(s) 20665-6

The cor. of secs. 22, 23, 26, and 27, monumented with an iron
post, 1¼ ins. diam., firmly set, projecting 16 ins. above
ground, (with 1 in. diam. drill steel projecting 14 ins above
ground driven alongside) with brass cap (properly) mkd.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which the remaining orig. bearing trees
A madrone, 17" diam., bears N.55°E., 16.5 ft., with a healed blaze. (Record, N.52°E.)

A madrone, 12" dia., bears S.18°E., 18.5 ft., no scribing visible on an opened blaze. (Record, S.20°E.)

A madrone, 12" dia., bears N.57°W., 32.3 ft., with a healed blaze. (Record, N.60°W., 36.3 ft.)

and bearing trees mkd. by Cole, reported by Jelley and Rogers

A fir, 34" dia., bears N.55¼°E., 70.5 ft., with a healed blaze. (Record, N.59½°W., 68.6 ft.)

A stump, 33" dia., bears S.78¾°W., 77.9 ft., with no marks visible. (Record, S.76½°W.)

A fir, 45" dia., bears N.43¼°W., 60.2 ft., with a healed blaze. (Record, N.45°W., 58.1 ft.)

and bearing trees mkd. by Powell, reported by Jelley & Rogers

A fir, 31" dia., bears S.¼°E., 23.5 ft., with fragmentary scribe marks visible on a partly healed blaze. (Record, S.3°E., 24.4 ft.)

A fir, 8" dia., bears S.53°W., 14.5 ft., with a healed blaze.

A fir, 12" dia., bears N.16½°W., 15.2 ft., with a healed blaze. (Record, N.20°W.)

The Jelley and Rogers record identifies the 1" dia. drill steel as the cor. point however, the county record is clear that the iron post when established was set at the corner point. Therefore, the iron post with brass cap is accepted as the corner point.