

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7973-74)

Set Fir post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Laurel 8" dia., bears S.58°W., 4 lks. dist., mkd. ¼ S BT
A Fir 28" dia., bears S.60°E., 29 lks. dist., mkd. ¼ S BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17293-94)

Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
T 31 S R 6 W
1/4
S 22 | S 23
1980

from which
A Fir 6" dia., bears S.88°E., 40 lks. dist. mkd. ¼ S23 BT.
A Fir 10" dia., bears N.55½°W., 67 lks. dist. mkd. ¼ S22 BT.

From this point, United States Geological Survey triangulation station SILVER BUTTE Reference Mark No. 2, bears S.62°25'E., 41.41 chs. dist., monumented with a brass cap, 3" dia., set in a concrete footing, 3 x 3 x 3 ft. sq. at the southwest corner of lookout tower, with brass cap mkd. SILVER BUTTE No 2 1942 with an arrow pointing to the corner. The triangulation station has been removed or destroyed.

Found OK by Lang, April 1995 - M125-3

Douglas County Surveyors Office - Randall Smith & Stephen Flause - C.S. 64/69-14 - July 15, 1996

Found - 3¼" Dia. Brass cap on a 2½" o.d. iron pipe protrudes 5" above ground.
11" dia. D.Fir, with a fully healed single blaze, bears S.88°E., 25.7'.
11" dia. D.Fir, with a fully healed single blaze, bears N.55½°W., 43.5'.
New - 7" dia. D.Fir, double blazed and scribed "¼ S23 CS BT", bears N.6½°E., 5.2'.
10" dia. D.Fir, double blazed and scribed "¼ S22 CS BT", bears S.38½°W., 9.5'.

Continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and
Jeff Lorsung - 3/19/25 - C.S. File 67/60-8

Found - 3/4" BLM brass cap found per record.
18" D.Fir S.88°E 26.0' (rec 25.7') fully healed
single blaze.
13" D.Fir N.55¼°W. 43.0' (rec 43.5') fully healed
single blaze.
11" D.Fir N.6½°E. 5.2' fully healed double blaze.
14" D.Fir S.38½°W. 9.5' fully healed double blaze.
Added 3/2" mag nails right side center to all
bearing trees.

Notes - Mon is approx 70' east of gravel road.
Compass decl. 14½°E.
OCS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N 449164.706 E 4147338.812