

PRIMARY CORNER DESCRIPTION Sec Cor for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7974)

Set a Maple post 4 ft. long, 4" sq., 22" in the ground, for cor. to secs. 14, 15, 22 and 23, mkd. T31S R6W S14 on NE.; S23 on SE.; S22 on SW.; and S15 on NW. faces, with 2 notches on E. and 3 notches on S. edges, from which

A Fir 30" dia., bears N.21°E., 25 lks. dist. mkd. T31S R6W S14 BT.

A Laurel 7" dia., bears S.60°E., 73 lks. dist., mkd. T31S R6W S23 BT.

A Fir 36" dia., bears S.50°W., 8 lks. dist., mkd. T31S R6W S22 BT on SW.

A Fir 26" dia., bears N.60°W., 40 lks. dist., mkd. T31S R6W S15 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby, Wm. Stoffel, crew - March 19, 1963 - C.S. 52/25-15

Found - Orig. 36" now rotted base of large Fir, S.50°W., 5.3' Orig. 7" now 12" Laurel snag S.60°E., 48.2 ft. shows scribing.

Orig. 26" now 40" Fir N.60°W., 26.4 ft. shows good bark scribing.

Orig. 30" now 40" Fir N.21°E., 16.5 ft.

Set Brass cap alongside found scribed corner stake, cap mkd:
County Surveyors Office

T 31 S R 6 W
S 15 | S 14
S 22 | S 23
1963

New BTs -15" R.Fir bears S.68°E., 12.7 ft. scribed S23 T31S R6W CS BT.

6" R.Fir bears N.2°E., 19.4 ft. scribed S14 CS BT.

18" R.Fir bears S.20°W., 6.0 ft. scribed T31S R6W CS BT.

Brass cap, 1 orig. BT and 3 BTs by Bryon, Fd. and used in BLM survey by Jelley and Rogers, under Group #1042, surveyed Oct. 1980-Oct. 1981 (DCSO records, Vol. 45 Page 17295)

Found OK by Lang, April 1995 - M125-3

continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 14, 15, 22 and 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2300, Surveyed March/April 2008 - (DCSO records Vol. 56 Page(s) 22172)

The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 1¼" dia., firmly set, projecting 13" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir, 45" dia., bears N.21°E., 16.5 ft., with no marks visible.

A decayed fir stump, size indeterminate, bears S.50°W., 5.3 ft., with no marks visible.

A fir, 44" dia., bears N.72¾°W., 26.4 ft., with no marks visible. (Record, N.60°W.)

and BTs mkd. by Byron, in 1963, reported by Jelley and Rogers

A fir, 9" dia., bears N.2°E., 19.5 ft., with no scribe marks visible on a partially healed blaze.

A fir, 18" dia., bears S.68°E., 12.5 ft., with a healed double blaze.

A fir, 25" dia., bears S.19°W., 6.3 ft., with a healed double blaze.

Corner is located on an E. slope, 65 ft. N. of a draw, drains N.45°E.

The geographic position (NAD 1983 (CORS 96)) of the following corners, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, using for control National Spatial Reference System Continuously Operating Reference Station (CORS) CAPE BLANCO CORS ARP (CABL), and National Cooperative CORS Network Station ROSEBURG COOP CORS ARP (DCSO), is as follows:

The corner of sections 14, 15, 22, and 23.

Latitude: 42°52'11.64"N. Longitude: 123°23'14.46"W.