

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7975)

-----  
 Set Laurel post, 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor. mkd. 1/4 S on W. face, from which  
 A Fir 38" dia., bears N.30°E., 36 lks. dist. mkd. 1/4 S BT.  
 A Laurel 5" dia., bears N.85°W., 9 lks. dist. mkd. 1/4 S BT

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell, Wm. Stoffel, M. Stone, crew - Aug. 31, 1962 - C.S. File 52/25-14

-----  
 Found - Orig. 5", now dead, Laurel S.58°W., 2.6 ft., shows scribing.

SE Bearing tree, down.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 6 W

1/4 S15 | S14

1962

New BTs -14" R.Fir bears S.48°E., 15.6 ft. scribed 1/4 S14 CSBT  
 13" R.Fir bears S.28°W., 7.6 ft. scribed 1/4 S15 CSBT.  
 Corner is 80 ft. West of logging road.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - June 17, 1996 - C.S. 64/69-4

-----  
 Mon. Fd.- 2 1/2" Brass cap on a 1 1/2" O.D. iron pipe, protrudes 17" above ground.

Bt's Fd.- Orig. NW BT now gone, a possible root hole? near orig. brg. & dist. (Orig- rec N.85°W., 5.9')  
 DCSO 1962 rec. is S.58°W., 2.6'?

54" DIA. 6' high burnt on blaze side D.Fir Stump, no scribing found, bears N.30°E., 25.5'.

22" DIA. D.Fir with a fully healed double blaze, bears S.84°E., 15' (DCSO 1962 rec. is S.48°E.?, 15.6' per C.S. 52/25 & BT tag) Rec. dist is 15.6' at center of trunk. 1962 DCSO.

17" DIA. D.Fir with a fully healed double blaze, bears S.28°W., 7.6'.

No OBT was marked in SE Quad as stated in 1962 DCSO Renewal "Down Tree"?

Mon. Set- BC/IP is surrounded by a 2' dia. mound of stone.  
 New BT's- 11" dia. D.Fir double blazed and scribed "1/4 S14 CS BT", bears N.8 1/2°E., 21.4'.

9" dia. D.Fir double blazed and scribed "1/4 S15 CS BT", bears N.25 1/2°W., 14.7'.