

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7977)

Set Fir post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Cedar 24" dia., bears N.50°E., 18 lks. dist. mkd. ¼ S BT
A Fir 5" dia., bears N.60°W., 23 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John Powell, Frank Jones, Cliff Stone, crew - Oct. 1966 - C.S. File 54/31-16

Found - Orig. 27" now 38" Cedar, N.50°E., 11.9 ft. burnt out, no scribe visible.
Orig. 5" now D.Fir snag, N.60°W., 15.2 ft. opened for scribing "BT"

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 6 W
¼ S10 | S11
1966

New BT - 20" D.Fir N.19°W., 24.0 ft. mkd. ¼ S10 CS BT.
Reblazed and rescribed:
38" Cedar N.50°E., 11.9 ft. mkd. ¼ S11 CS BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17296-97)

The ¼ sec. cor., perpetuated by Powell in 1966, as described in a Douglas County Surveyor's record, monumented with an iron post, 1¼" dia., firmly set, projecting 16" above ground with 1966 brass cap
from which the remains of an original bearing tree
A Fir stump 10" dia., bears N.60°W., 23 lks. dist., with scribe marks BT visible on opened blaze.
and new bearing trees
A Fir stump 26" dia., bears S.8°E., 16 lks. dist., mkd. ¼ S11 BT.
A Fir 12" dia., bears N.19°W., 85 lks. dist., mkd. ¼ S10 BT.

The cor. is located in a clear cut. No other suitable trees available within limits.

Fd. Ok by K. DeGroot, May 2004 - M146-5