

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 524300

PRIMARY CORNER DESCRIPTION AP 1 on Line between Secs. 23 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - J.W. Cole, Co. Surveyor - For:
J. E. Reeves - Feb. 1924 - Survey Vl. 3 Page 181-182

Set 1"x40" drill steels on the true line at points 1115.0
ft., & 1236.7 ft. & 1596.7 ft. East of the beginning point
(Cor. Secs. 22, 23, 26, & 27) to mark the secs. line where it
passes over a ledge of mineral ore.

BLM dependent resurvey by A. Bert Skeesick & Timothy Moore,
Cadastral Surveyors under Group #1950, surveyed April/May
2000 (DCSO rec. Vol. 53 Page"(s) 20664

A point established on the line bet. secs. 23 & 26 by Cole,
in 1924, monumented with a drill steel, 1" diam., firmly set,
projecting 5" above ground. This point is accepted as marking
the sec. line and is identified as Angle Point No. 1. Placed
an aluminum cap, 2" diam., on top of drill steel, mkd.

T 31 S R 6 W

AP1 S 23
S 26
2000