

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7971)

Set a Yew post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which

A Fir 48" dia., bears S.85°W., 15 lks. dist., mkd. ¼ S BT

A Fir 8" dia., bears N.54°W., 40 lks. dist., mkd. ¼ S BT.

George Wenderoth - Nov. 18, 1959 - C.S. File 49/92

Found - 50" Fir S.88°W., 9.9 ft. bark scribed but dead and broken off.

Other tree gone.

Drive 1" Iron pipe and scribe new trees:

14" Fir S.54°16'E., 13.5 ft.

22" Maple N.46°05'W., 65.8 ft.

Douglas Co. Surveyors Office - John Powell, Frank Jones, Cliff Stone, crew - Oct. 7, 1966 - C.S. File 54/31-20

Found - 1" Iron pipe at ¼ corner.

Orig. Fir snag, S.85°W., 9.9 ft. no scribe visible.

14" Fir S.54°E., 13.5 ft. scribe visible ¼ S35 CS BT

(I find this tree to be a Yewwood, dist. to face of tree.)

No trace of NW Maple BT.

Unrecorded 20" D.Fir N.36°W., 65.6 ft., opened for scribe ¼ S26 CS BT. (By ring count, I find scribing on D.Fir to be 1959, 7 yrs. This is the time Wenderoth renewed this corner.

Alongside Iron pipe, Set Brass cap at ¼ sec. cor. marked:

County Surveyors Office

T 31 S R 6 W

¼ S 26

S 35

1966

Survey by Glenn S. Baughman L.S. #536 - For: Conifer Logging - March 1984 - M 96-32

Found - County Surveyors brass cap.

50" Fir snag bears S.85°W., 9.9 ft. (Orig.)

17" Yew bears S.54°E., 14.0 ft.

24" D.Fir bears N.36°W., 65.6 ft. (uprooted)

New BT - 6" D.Fir bears N.23½°E., 41.5 ft. (I scribed)

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ron Quimby - Crew: N. Fromdahl & R. Olson - 11/17/2016 - C.S.
File 65/93-57

Found - 1966 DCSO brass cap
50" D.Fir snag S.85°W., 9.9 ft. (Orig. BT)
18" Yewwood S.54°E., 14.0 vis. scribe.
14" D.Fir N.23½°E., 41.5 ft. good scar.
New - 10" D.Fir S.63°W., 23.8 ft. scribed ¼ S35 BT.
12" D.Fir N.42°W., 31.8 ft. scribed ¼ S26 BT.
15½°E Decl.