

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7973)

Set a Fir post, 30" long, 3" sq., in a mound of stone for the 1/4 sec. cor. mkd. 1/4 S on N. face. No trees convenient and pits impracticable.

J. W. Cole - For: J.E. Reeves - Feb. 11-16, 1924 - Vol. 3 Pg. 181; Field Book 52 Pgs. 40-45; (and "old" corner book, page 163)

Could find no evidence of original corner.
Established corner midway on true line between section corners.
Set a 1" x 40" drill steel, also a fir post properly marked for the 1/4 corner, from which
 A ledge rock bears S.64°00'W., 70.0 ft. marked 1/4 S CS B0.
 A Fir 36" dia., bears West, 14 ft. mkd. with two notches on the East and West faces.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey, Clete Putnam, crew - June 1961 - C.S. File 52/25-8

Found - 1" drill steel at corner.
 36" now 40" Fir snag, West, 14.0 ft.
 B.O. not found.
New BTs -8" R.Fir bears S.54°W., 49.7 ft. scribed 1/4 S26 CSBT
 17" R.Fir bears N.5°E., 48.6 ft. scribed 1/4 S23 CSBT

Douglas Co. Surveyors Office - Randall Smith, Deputy, Stephen Flause, crew - March 28, 1984 - C.S. File 62/16-20

Found - 1" drill steel protruding 4" above ground.
 36" Fir now a 40" dia., 25 ft. high snag, with two notches on East side and one notch on West side, bears N.84°W., 15.7 ft. (Rec. West, 14.0 ft., dist. is to East side of BT)
 8" R.Fir now a 17" D.Fir with a well healed single blaze bears S.54°W., 49.7 ft.
 17" R.Fir now a 24" D.Fir with a well healed double blaze bears N.5°E., 48.6 ft.
Set DCSO disk on a 1" x 30" I.Pipe protruding 3" above ground with 1" drill steel alongside. Cap mkd: "Douglas County Surveyors Office T31S R6W 1/4 S23 S26 1984"
No new accessories. Corner lies on steep rocky East slope.

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The ¼ sec. cor. of secs. 23 & 26, reestablished by proportionate measurement by Cole, in 1924, perpetuated by Byron, in 1961, and further perpetuated by Smith & Flause, in 1984. There is no remaining evidence of the original corner; therefore, this position is accepted as the corner, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 6" above ground, in a mound of stone, 2 ft. base, 1 ft. high, (with 1" diam. drill steel projecting 4" above ground driven alongside) with brass cap (properly) mkd. from which the remains of the bearing tree mkd. by Cole

A decayed fir stump, 23" diam., bears N.82°W., 14.0 ft., no marks visible.

and bearing trees mkd. by Byron

A fir, 28" diam., bears N.3°E., 48.6 ft., with a healed double blaze.

A fir, 22" diam., bears S.52¼°W., 49.7 ft., with a healed blaze.

From this point, U.S. Coast and Geodetic Survey triangulation station "SILVER BUTTE 1942" bears N.6°10'08"W., 1439.75 ft. (mean bearing and sea level), monumented with a standard brass cap, 3½" diam., firmly cemented into a drill hole in a rock outcrop, with top mkd. SILVER BUTTE 1942 and a triangle.