

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7978)

Set a stone 20x10x5, 12" in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which
 A Live Oak 12" dia., bears N.4°W., 69 lks. dis. mkd. ¼ S BT
 A Live Oak 5" dia., bears S.15°E., 25 lks. dis. mkd. ¼ S BT

John Markham, Jr. - For: Logsdon Bros - Wit: George and Bill Vaughn - Dec. 1949/Jan. 1950 - C.S. File 40/233

As determined from remains of O.B.T.:
 An Ash (not Oak) 8" dia. which bears S.15°E., 16.5 ft. (A notation made later said "live 8 Oak, HM" and another says "field notes say Ash")
At corner set 3/4" x 24" I.P. 12" in the ground, from which
 10" Fir bears N.27°E., 17.0 ft. mkd. ¼ S 2880 BT.
 6" Fir bears S.4°W., 8.6 ft. mkd. ¼ S 2880 BT.
This corner sets just West of an 80 ft. rock bluff.

Fd. OK by R.Brown, April 1995 - M 119-61
Fd. Ok by K. DeGroot, Feb. 2005 - M146-18

Ron Quimby - For: C & D Lumber Co. - 3/2016 - M171-7

Found - 3/4" iron pipe per 1950 renewal
 8" Ash, now 10", bears S.15°E., 16.5'
 10" fir, now 23", bears N.27°E., 17'
 6" fir, now 10" snag, bears S.4°W., 8.6'
New - 8" madrone bears N.82°W., 12.5', scribed "¼ S2 BT"