TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7957)

Set a Chinkapin post, 3 ft. long, 3" sq., 15" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Chinkapin 8" dia., bears S.40°E., 8 lks. dist.
A Laurel 14" dia., bears S.60°W., 20 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - For: C & D Lumber Co. - April 2, 1963 - C.S. File 53/12; M 25-10

Set Brass cap at ¼ cor. mkd: County Surveyors Office, 1963
¼ S35 S36 T31S R6W
New BTs -15" R.Fir bears N.23°E., 28.5 ft. scribed ¼ S36 CS BT.
5" Cedar bears S.83°E., 40.3 ft. scribed ¼ S36 CSBT
6" Fir bears N.(?)W 24.9 ft. scribed ¼ S35 CS BT.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause - July 16, 1996 - C.S. 64/69-18

Mon. Fd.- 2½" Brass cap on a 1½" o.d. iron pipe, bent 1' west protruding 18" above ground.

Bt's Fd.- Measurements taken from plumb position of BC/IP
16" dia. 4' high D.Fir stump, with a partially healed upper blaze, scribing visible "4 S36 CS" lower blaze is healed, bears N.23°E., 27.7'.
6" dia. down and rotted cedar, with scribing visible on a paritally healed double blaze "¼ S35 CS BT" rotted root crown bears S.83°E., 40.3'.
A search was made for the 6" Fir at a bearing as shown above N?W, 24.9' no evidence found (Note: area around corner is heavily brush covered).

Mon. Set- Plumb position of BC/IP is referenced, BC/IP is removed and straightened (measures 36" long). BC/IP is set at referenced position, protrudes 8" above ground.

New BT's- 3" dia. D.Fir double blazed and scibed "X BT", bears S.73°W., 10.2'.
60" dia. 3' high D.Fir stump with a 6" boat spike through a BT tag set near top center of stump. Boat spike bears N.42°E., 17.6'.
4" dia. D.Fir double blazed and scribed "X BT", bears N.80½°E., 6.2'.

corner lies approx east, 110' from the intersection of a gravel road and dirt road.