

PRIMARY CORNER DESCRIPTION Sec Cor for 25, 26, 35 and 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7957-58)

 Set Sugar Pine post, 4 ft. long, 4" sq., 22" in the ground for cor. to secs. 25, 26, 35 and 36 mkd. T31S R6W S25 on NE. S36 on SE.; S35 on SW and S26 on NW. faces with 1 notch on S. and E. edges, from which

- A Fir 18" dia., bears N.36°E., 17 lks. dist. mkd. T31S R6W S25 BT.
- A Fir 24" dia., bears S.55°E., 56 lks. dist., mkd. T31S R6W S36 BT.
- A Fir 36" dia., bears S.55°W., 80 lks. dist., mkd. T31S R6W S35 BT.
- A Fir 30" dia., bears N.15°W., 13 lks. dist., mkd. T31S R6W S26 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey, Clete Putnam, crew - June 1961 - C.S. File 52/25-11

 Found - Orig. 24" now 36" R.Fir S.65°E., 37.0 ft., shows old bark scribing "BT T31"
 Orig. 30" now 40" Fir N.15°W., 8.6 ft. old face axed off, no scribing found.
 Orig. 36" now 40" Fir S.55°W., 52.8 ft., old face axed off, no scribing found.
 No trace of original NE BT found.

This corner renewed recently but not recorded. Orig. SW and NW BTs rescribed. Also same person scribed a 7" Fir bears S.31°E., 25.2 ft. and a 50" R.Fir bears N.31°E., 46.7 ft.
 Set Brass cap at cor. mkd: County Surveyors Office

T 31	S R 6	W
S 26		S 25
S 35		S 36
1961		

New BTs -6" R.Fir bears S.23°W., 18.6 ft. scribed S35 CS BT
 6" R.Fir bears N.50°E., 79.7 ft. scribed S25 CS BT

Douglas Co. Surveyors Office - John Powell, Frank Jones and Cliff Stone, crew - Oct. 1966 - C.S. File 54/31-19

 Found - 1961 Co. Brass cap at cor. marked accordingly.
 Orig. 36" Fir, now stump, S.65°E., 37.0 ft.
 Orig. 40", now stump, (Fir) S.55°W., 52.8 ft.
 7" Fir now snag, S.31°E., 25.2 ft. shows pitched over face.
 Orig. 40" Fir, now 40", N.15°W., 8.6 ft. scribe marks visible.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 25, 26, 35 and 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

50" Fir N.51°E., 46.7 ft., shows pitched over scribing.
6" now 7" D.Fir S.23°W., 18.6 ft., shows good scar.
6" now 7" D.Fir N.50°E., 79.7 ft., shows good scar.
New BT - 7" D.Fir S.24°W., 27.3 ft scribed T31S R6W S36 CS BT

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2078, surveyed June/Sept. 2004 (DCSO rec. Plat 31-6 2011 & Vol. 56 pg(s) 22323)

The cor. of secs. 25, 26, 35, & 36, perpetuated by Byron in 1961, further perpetuated by Powell in 1966, monumented with an iron pipe, 1½" dia., firmly set, projecting 20" above the ground, with brass cap (properly) mkd. from which the remains of the orig. BTs

A sawed, decayed fir stump, 44" dia., bears S.63°E., 35.0 ft. with no marks visible (Rec. S.55°E., 37.0 ft.)

A sawed, decayed fir stump, 44" dia., bears S.58¼°W., 52.8 ft. with no marks visible (Rec. S.55°W.)

A fir, 42" dia., bears N.19°W., 10.1 ft. with a healed double blaze. (Rec. N.15°W., 8.6 ft.)

and the remains of a BT mkd by persons unknown, reported by Byron

A sawed, decayed fir stump, 52" dia., bears N.29½°E., 47.2 ft. with no marks visible.

and the BTs mkd. by Byron

A fir, 19" dia., bears N.50°E., 78.9 ft. with a healed double blaze.

A fir, 17" dia., bears S.20¼°W., 17.8 ft no marks visible.

and the remains of a BT mkd by Powell

A fir stump, 9" dia., bears S.23¼°E., 26.8 ft. with fragmentary scribe marks visible.

and a new BT

A fir, 9" dia. bears S.32°E., 30.8 ft mkd: T31S R6W S36 BT
From this point, an iron pipe, ¾" dia., firmly set, projecting 13" above the ground, with no cap, set by person(s) unknown, bears North, 0.4 ft.

Fd. Ok by R. Quimby, 11/2016 - C.S. File 65/93-56