

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7959)

-----  
Set Fir post, 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which  
A Fir 30" dia., bears S.5°E., 36 lks. dist. mkd. 1/4 S BT.  
A Fir 14" dia., bears N.30°W., 47 lks. dist., mkd. 1/4 S BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam, crew - June 1, 1961 - C.S. 52/25-10

-----  
Found - Orig. 30" now 40" R.Fir, S.5°E., 23.8 ft., shows good bark scribing "1/4S BT". No trace of orig. NW BT found.

Set Brass cap at cor. mkd: County Surveyors Office, 1961  
1/4 S26 | S25 T31S R6W  
New BTs -16" R.Fir bears N.85°E., 26.8 ft. scribed 1/4 S25 CS BT  
14" R.Fir bears N.85°E., 65.0 ft. scribed 1/4 S25 CS BT.

No live trees near to West.

Survey by Glenn S. Baughman, L.S. #536 - For: Conifer Logging - March 1984 - M 96-32

-----  
Found - County Surveyors brass cap.  
20" D.Fir stump bears N.85°E., 26.8 ft.  
18" D.Fir stump bears N.85°E., 65.0 ft.  
New BTs -13" Hemlock bears N.8 3/4°E., 130.8 ft. (I scribed)  
9" D.Fir bears N.72 1/2°W., 96.2 ft. (I scribed)

Found OK, July 1995 by B.Shaner - M122-23; Corner reports filed in C.S. 63/161-31 thru 35.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2078, surveyed June/Sept. 2004 (DCSO rec. Plat 31-6 2011 & Vol. 56 pg(s) 22323)

-----  
The 1/4 sec. cor. of secs. 25 & 26, perpetuated by Byron in 1961, further perpetuated by Baughman in 1984, monumented with an iron pipe, 1 1/4" dia., firmly set, projecting 9" above the ground, with brass cap (properly) mkd from which the remains of an orig. BT

A roothole, bears S.5°E., 23.8 ft. alongside of which is the fir trunk, 44" dia., with no marks visible. and the remains of BTs mkd by Byron

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A sawed fir stump, 20" dia., bears N.85¼°E., 26.8 ft. with a healed double blaze.  
A sawed fir stump, 17" dia., bears N.85°E., 64.9 ft. with a healed double blaze.  
and BTs mkd by Baughman  
A hemlock, 23" dia., bears N.9°E., 130.7 ft. with a healed double blaze.  
A fir, 23" dia., bears N.73°W., 96.3 ft. with a healed double blaze.

Ron Quimby - Crew: N. Fromdahl & R. Olson - 11/17/2016 - C.S.  
File 65/93-58

-----

Found - DCSO brass cap  
20" capped Fir stump N.85¼°E., 26.8 ft healed blaze.  
25" Hemlock N.9°E., 130.2 ft. healed face.  
27" Fir N.73°W., 96.3 ft. healed face.

New - 14" D.Fir S.85°W., 31.9 ft. scribed ¼ S26 BT.  
15¼° Decl.