

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7962)

-----  
Set Fir post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 13, 14, 23 and 24 mkd. T31S R6W S13 on NE.; S24 on SE.; S23 on SW.; and S14 on NW. faces, with 1 notch on E. and 3 notches on S. edges, from which

A Fir 40" dia., bears N.32°E., 45 lks. dist. mkd. T31S R6W S13 BT.

A Fir 36" dia., bears S.71°E., 28 lks. dist. mkd. T31S R6W S24 BT.

A Laurel 8" dia., bears S.20°W., 20 lks. dist. mkd. T31S R6W S23 BT.

A Chinkapin 6" dia., bears N.30°W., 10 lks. dist. mkd. T31S R6W S14 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Wm. Stoffel; M. Stone, crew - Aug. 31, 1962 - C.S. File 52/25-13

-----  
Found - Orig. 8" now 10" Laurel S.20°W., 13.2 ft. shows good scribing.

Orig. 36" now 46" Fir S.71°E., 18.5 ft. no scribing.

Orig. 40" now 50" R.Fir N.32°E., 29.7 ft. shows scar

Do not find NW bearing tree.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 6 W

S 14 | S 13

S 23 | S 24

1962

Corner is 50 ft. South of logging road.

New BTs -Rescribe O.B.T., now 46" R.Fir S.73°E., 21.0 ft. S24 T31S R6W CS BT.

8" R.Fir bears S.72°W., 33.2 ft. scribed S23 T31S R6W CS BT.

No trees near to Northwest.

Cor. Fd. OK, DCS Office, John Powell, Oct. 1966 C.S. 54/31-13

Bruce Shaner, L.S. #430 - For: Richard McKenzie - John Wright & Clem Berlier, crew - Oct 1993 - M 117-76 - C.S. 63/153-41

-----  
Found - 2½" Brass cap on a 1" iron pipe from which;  
10" madrone, scribes visible, bears S.20°W., 13.2'.  
46" D.Fir, scribes visible, bears S.73°E., 21.0'.  
50" D.Fir, now blown down & gone, bears N.32°E., 29.7'.

(Cont. Next Page)

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" D.Fir, face overgrown, bears S.72°W., 33.2'.  
New BT - 6" Chinquapin, scribed, "T31S, R6W, S14, BT", bears  
N.3°W., 22.0'.  
No trees near in NE Quadrant.  
Corner is 50' South of main logging & mining road.

BLM Dependent resurvey by Timothy J. Moore, Cadastral  
Surveyor & Robert H. Browning, Surveying Tech. under Group  
#2078, surveyed June/Sept. 2004 (DCSO rec. Plat 31-6 2011 &  
Vol. 56 pg(s) 22324)

-----  
The cor. of secs. 13, 14, 23, & 24, perpetuated by Byron in  
1962, further perpetuated by Shaner in 1993, monumented with  
an iron pipe, 1½" dia., firmly set, flush with a mound of  
stone, 2 ft. dia., 18" high, with brass cap (properly) mkd.  
from which the remains of the orig. BTs

A fir snag, 43" dia., bears S.71°E., 18.5 ft. with scribe  
marks T31S R6W S24 CS visible on open upper blaze and  
BT visible on lower open blaze. (Rescribed by Byron)

A madrone, 12" dia. bears S.13¾°W., 12.3 ft. with no marks  
visible. (Rec. S.20°W., 13.2 ft.)

And a BT mkd by Byron

A fir 13" dia., bears S.69¾°W., 33.0 ft. with a healed  
double blaze.

and a BT mkd by Shaner

A chinquapin, 9" dia., bears N.6¾°W., 21.5 ft. with a  
healed double blaze.

and new BTs

A fir, 28" dia., bears N.78¼°E., 27.2 ft., mkd: T31S R6W  
S13 BT.

A fir, 4" dia., bears S.16°E., 6.1 ft., mkd: X BT.

Latitude 42°52'10.54"N.

Longitude 123°22'03.23"W.

(NAD 1983 (COR96))

Gregg Neitsch - For: Silver Butte Tbr Co. - 2/2024 - M183-41

-----  
Found - 1" I.D GIP with a 2½" BC stamped "COUNTY SURVEYORS  
OFFICE T31S R6W S14 S13 S23 S24 1962", 20" above  
ground, in a 2 ft diam stone mound, as shown  
(rec), from which bears

43" DF snag with vs S.73½°E., 19.9' (S.71°E., 18.5)

14" MD with HB S.13¾°W., 12.3'

18" DF with HB S.69¾°W., 33.0'

12" Chinquapin snag w/visible scribe N.6¾°W., 21.5'

30" DF with HB N.78¼°E., 27.2'.