

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7969)

Set a Laurel post, 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which
A Fir 18" dia., bears N.75°W., 67 lks. dist., mkd. 1/4 S BT
A Fir 30" dia., bears S.73°E., 64 lks. dist., mkd. 1/4 S BT

BLM resurvey by Lynn Roseberry and Albert Garrison, under Group #695, surveyed June 1969 (DCSO records Vol. 36 Page(s) 14879-80)

Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked
T 31 S R 6 W
1/4
S 2 | S 1
1969

from which
A Madrone 7" dia., bears S.86 1/2°E., 43 1/2 lks. dist., mkd. 1/4 S1 BT.
A Madrone 6" dia., bears S.56°W., 54 lks. dist., mkd. 1/4 S2 BT.
The corner is located on a steep hillside, slopes NE.; also edge of timber, bears NW. and SE.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 20, 1980-Oct. 19, 1981 (DCSO records Vol. 45 Page(s) 17291)

The 1/4 Sec. cor., monumented with an iron post, 2 1/2" dia., firmly set, projecting 4" above ground with brass cap mkd. T31S R6W 1/4 S2 | S1 1969

from which the remains of bearing trees mkd. by Roseberry and Garrison

A Madrone snag 8" dia., bears S.86 1/2°E., 43 1/2 lks. dist., with scribe marks 1/4 S1 BT visible on open blaze.

A Madrone snag 8" dia., bears S.56°W., 54 lks. dist., with scribe marks 1/4 S2 BT visible on open blaze.

and new bearing trees

A Fir 9" dia., bears S.85°E., 56 lks. dist., mkd. 1/4 S1 BT.

A Fir 9" dia., bears N.83°W., 53 lks. dist., mkd. 1/4 S2 BT.

Fd. Ok by R.Brown, April 1995 - M 119-61

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Ron Quimby - For: C & D Lumber Co. - 3/2016 - M171-7

Found - Brass cap per 1969 renewal
9" fir, now 21", bears S.85°E., 37'
9" fir, now 20" stump, bears N.83°W., 35'
New - 13" fir bears N.63°E., 20' scribed "¼ S1 BT"
6" fir bears N.25°W., 28.4' scribed "¼ S2 BT"
4" fir bears S.42°W., 23.5' scribed "¼ S2 BT"