

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36 T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7192)

-----  
Set post, cor. of secs. 1, 2, 35 and 35, from which  
A Laurel 15" dia., bears S.83°E., 34 lks.  
A Laurel 16" dia., bears N.36°W., 41 lks.  
A Laurel 16" dia., bears N.33°E., 68 lks.  
A Laurel 6" dia., bears S.5°W., 81 lks.

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7968-69)

-----  
Intersect Tp. line, 30 lks. W of cor. to secs. 1, 2, 35 and 36, which I re-established as per notes furnished, bearing trees all standing viz. Set a post, 4 ft. long, 4" sq., 22" in the ground for the cor. marked T30S R6W S36 on NE.; T31S S1 on SE.; S2 on SW.; and S35 on NW. face, with 1 notch on E and 5 notches on W. edges, from which  
A Laurel 16" dia., bears N.33°E., 68 lks. dist. mkd. T30S R6W S36 bT.  
A Laurel 15" dia., bears S.83°E., 34 lks. dist. mkd. T31S R6W S1 BT.  
A Laurel 6" dia., bears S.5°W., 81 lks. dist. mkd. T31S R6W S2 BT.  
A Laurel 16" dia., bears N.36°W., 41 lks. dist. mkd. T30S R6W S35 BT.

John H. Markham, Jr. - Feb. 15, 1950 - C.S. File 40/231-1

-----  
Determined from O.B.T.s  
33" Laurel bearing S.83°E., 23.0 ft. - remark "S1 2880 BT"  
16 Laurel bearing S.5°W., 54.0 ft. - remark "S2 2880 BT."  
24" Laurel bearing N.29°W., 39.0 ft. - remark "S35 2880 BT"  
At cor. point, found 1½" I.Pipe and set 1" x 30" Iron pipe 15" in ground from which  
10" Fir bears N.55°E., 41.0 ft. mkd. S36 2880 BT.  
There are fences running N-S and W from this corner.

Fd. OK, May 1969 - J.M.P. - M 37-62

BLM resurvey by Roseberry and Garrison, under Group #695. Surveyed June 1969 (DCSO records, Vol. 36 Pages 14880-81)

-----  
Found corner monumented with an I.P. 1½" dia., firmly set 6" above ground, alongside of which is another I.P. 1" dia., firmly set 6" above ground, from which the remains of the original bearing trees:  
(Cont. Next Page)

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36 T30-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Madrone 40" dia., bears S.81½°E., 37 lks. with scribe mark S visible on opened blaze. (Rec. S.83°E., 34 lks.)  
A Madrone 18" dia., bears S.3½°W., 81 lks. with scribe marks S2 2880 BT on bark. (Rec. S.5°W.)  
A Madrone 27" dia., bears N.30½°W., 55 lks. with scribe marks S35 2880 BT on bark. (Rec. N.36°W., 41 lks.)

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T	30	S	R	6	W
	S	35		S	36
	S	2		S	1
	T	31		S	
					1969

from which new bearing trees

A Fir 7" dia., N.87°E., 80 lks. mkd. T30S R6W S36 BT.

No other trees available within limits.

Reset the Iron pipes alongside the iron post.

Fd. OK, June 29, 1978, DCS0, C.S. file 60/11-26

Brass cap and 4 BTs, Fd. OK, by BLM dependent resurvey by Jelley & Rogers, under Group #1042. Surveyed Oct. 1980/Oct. 1981 (DCS0 records, Vol. 45 Pages 17290-91)

Fd. OK, March 1986, Donald Bentz, M 101-1

Fd. Ok by R.Brown, April 1995 - M 119-61

Fd. Ok by R.Brown, May 2004 - M 146-7

Fd. as per rec. by B. Knapp - 7/2016 - M172-52 A&B