

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7959)

Set a Laurel post, 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. marked ¼ S. on N. face, from which
A Laurel 4" dia., bears S.30°E., 10 lks. dist., mkd. ¼ S BT
A Laurel 4" dia., bears N.35°W., 15 lks. dist., mkd. ¼ S BT

George J. Wenderoth - Jan. 1962 - C.S. File 49/92

No sign of old original corner so placed new corner halfway between section corners, both being found.
Placed 1" Iron pipe for corner.
Scribed -10" Yew S.77°E., 37.5 ft.
10" Maple S.78°W., 17.5 ft.

Survey by Bruce Shaner, L.S. #430 - Wit: Mark Ramp; Brian Cameron - Dec. 7, 1981 - C.S. File 58/229-11

Found - 1" I.P., now buried and broken in half, lower half in position and OK.
10" Yew, scribes visible, now uprooted and down, but in position, bears S.77°E., 37.5 ft.
10" Maple, S.78°W., 17.5 ft. now gone.
Set 2" x 32" I.P. with 2½" Brass cap in place of 1" I.P., stamped "Shaner Engineering T31S R6W W.M. ¼ S25 S36 R.L.S. 430 1981". Reset 1" I.P. alongside brass cap.
New BTs -36" D.Fir stump BT, scribed "¼ S36 BT" bears S.84°E., 38.0 ft.
32" D.Fir stump BT, scribed "¼ S25 BT" bears N.24°W., 25.1 ft.
Corner is 150 ft. South of logging road, U.S.B.L.M. 31-6-26.0

Bruce Shaner, survey for Richard McKenzie, July 1995 - M122-23; C.S. File 63/161-35

Found corner same as described by Shaner in 1981.
Note - Set 6 ft. steel post, North 1.0 ft. Placed tag on USBLM road N.30°W., 120.0 ft.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2078, surveyed June/Sept. 2004 (DCSO rec. Plat 31-6 2011 & Vol. 56 pg(s) 22323)

The ¼ sec. cor. of secs. 25 & 36, reestablished by Wenderoth in 1962, perpetuated by Shaner in 1981 and is accepted as the cor. monumented with an iron pipe 2" dia., cont.

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

firmly set, projecting 8" above the ground with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Shaner

A sawed, decayed fir stump, 40" dia. bears S.82¼°E., 38.2 ft. with fragmentary scribe marks visible on an open blaze.

A sawed, decayed fir stump, 35" dia. bears N.24½°W., 25.0 ft. with fragmentary scribe marks visible on an open blaze.

and new BTs

A fir, 8" dia., bears N.0¼°E., 21.1 ft., mkd: ¼ S25 BT.

A fir, 8" dia., bears S.64¼°W., 8.0 ft., mkd: ¼ S36 BT.

Corner is located 85 ft. S of graveled road, 12 ft. wide, which bears N.60°W., & S.60°E.