

PRIMARY CORNER DESCRIPTION Center 1/4 Section 25

Alias	Description

Bruce Shaner, survey for Richard McKenzie, July 1995, M122-23; corner reports in C.S. File 63/161-31 thru 35.

Set - 2"x30" Iron pipe with a 3" Brass cap, marked:

T31S R6W
C $\frac{1}{4}$ + S25
RLS 430 1995

New Accessories -

- 8" D.Fir BT, I scribed "C $\frac{1}{4}$ S25 BT", bears N.38°E. 18.6 ft.
- 8" Pine BT, I scribed "C $\frac{1}{4}$ S25 BT", bears due East 14.0 ft.
- 10" D.Fir BT, I scribed "C $\frac{1}{4}$ S25 BT", bears S.7°E. 24.3 ft.
- 6" Pine BT, I scribed "C $\frac{1}{4}$ S25 BT", bears S.36°W. 3.7 ft.
- 6 ft. steel fence post bears West, 1.0 ft.

Note - Corner is 400 ft. South of USBLM Road. Tagged on road.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2078, surveyed June/Sept. 2004 (DCSO rec. Plat 31-6 2011 & Vol. 56 pg(s) 22324)

Point for the center $\frac{1}{4}$ sec. cor. of sec. 25 at the intersection with the E & W centerline.

Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, with brass cap marked:

T31S R6W
C $\frac{1}{4}$ S 25
2004

from which

A fir, 11" dia., bears S.17 $\frac{3}{4}$ °W., 24.8 ft., mkd: C $\frac{1}{4}$ S25 BT.

A fir, 12" dia., bears N.64 $\frac{1}{2}$ °W., 15.3 ft., mkd: C $\frac{1}{4}$ S25 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point a point established as the C $\frac{1}{4}$ sec. cor. of sec. 25 by Shaner in 1995 bears N.68°56'29"E., 28.31 ft. This point was not correctly positioned and is not utilized during the course of this survey, monumented with an iron pipe, 2 $\frac{1}{2}$ " dia., firmly set, projecting 10" dia., above the ground, with brass cap mkd. C $\frac{1}{4}$ S25 RLS 430 1995, from which BTs mkd by Shaner:

A fir, 13" dia., bears N.32 $\frac{3}{4}$ °E., 18.8 ft. with fragmentary scribe marks visible on a partially healed blaze.

A pine, 8" dia., bears N.87 $\frac{1}{4}$ °E., 13.9 ft. with scribe marks C $\frac{1}{4}$ S25 BT visible on a partially healed blaze.

A fir, 13" dia., bears S.9°E., 24.3 ft with a healed blaze

A pine, 6" dia., bears S.28 $\frac{3}{4}$ °W., 3.9 ft. with scribe marks C $\frac{1}{4}$ S25 BT visible on a partially healed blazes.