

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New Accessories -

12" D.Fir, Scribed "¼ S25 BT" bears S.46°E., 17.0'
6' steel fence post, South 0.5'.

Corner lies on steep North slope about 250' South of
creek & logging road.

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert H. Browning, Surveying Tech. under Group
#2078, surveyed June/Sept. 2004 (DCSO rec. Plat 31-6 2011 &
Vol. 56 pg(s) 22323)

The ¼ sec. cor. of secs. 24 & 25, reestablished by Shaner in
1964, perpetuated by Powell in 1966, further perpetuated by
Shaner in 1993, and is monumented with an iron rod, 5/8"
dia., firmly set, projecting 3" above the ground, lying on
the ground alongside of which is an iron pipe, 1¼" dia., 33"
long. Reset the iron pipe, 33" long. Reset the iron pipe, 33"
long, 27" in the ground, directly over the iron rod with
brass cap (properly) mkd.

from which the remains of BTs mkd by Shaner in 1964

A sawed fir stump, size indeterminate, bears S.72°W., 67.9
ft. with no marks visible.

A hemlock, 21" dia., bears N.36°W., 65.2 ft. with a healed
blaze.

and a BT mkd by Powell

A fir, 15" dia., bears N.82½°E., 33.9 ft. with a healed
double blaze.

and a BT mkd by Shaner in 1993

A fir, 26" dia., bears S.54½°E., 16.9 ft. with a healed
double blaze.