

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7963)

-----  
A stone 40x24x18 ins. which I marked ¼ on N. face for ¼ sec. cor., from which

A Fir 14" dia., bears N.25°W., 32 lks. dist., mkd. ¼ S BT

A Live Oak 12" dia., bears S.2°E., 32 lks., mkd. ¼ S BT.

Bruce Shaner - For: Richard McKenzie - John Wright & Clem Berlier, crew - Oct. 1993 - M 117-76 - C.S. File 63/153-42

-----  
Corner was surveyed in & set by proportioning, found distance & bearing with U.S. GLO records. See survey file, Douglas County Surveyor's Office.

Set 5/8" Iron Rod with 1½" Aluminum cap, stamped "SHANER ENGR. RLS 430", in steep, rocky cutbank of mainline logging road, (No way to install brass cap). From which,

10" D.Fir, scribed "¼ S13 BT" bears N.35°E., 32.4'.

10" D.Fir, scribed "¼ S13 BT" bears N.83°E., 40.6'.

14" D.Fir, scribed "¼ S24 BT" bears S.38°E., 41.4'.

10" D.Fir, scribed "¼ S24 BT" bears S.2½°W., 78.2'.

6' steel fence post, bears East, 0.5'.

Corner is on west cutbank of U.S. B.L.M. Road # 30-6-35.0.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2078, surveyed June/Sept. 2004 (DCSO rec. Plat 31-6 2011 & Vol. 56 pg(s) 22324)

-----  
The ¼ sec. cor. of secs. 13 & 24, reestablished by Shaner in 1993, and is accepted as the corner, monumented with an iron rod, 5/8" dia., firmly set, projecting 1" above the ground, with an alum. cap 1½" dia., affixed to top, mkd SHANER ENGR RLS 430, from which BTs mkd. by Shaner

A fir, 17" dia., bears N.31¾°E., 32.4 ft. with a healed blaze.

A fir, 13" dia., bears N.79°E., 40.5 ft. with fragmentary scribe marks visible on a partially healed blaze.

A fir, 18" dia., bears S.39¾°E., 41.9 ft. with a healed blaze.

A fir, 16" dia., bears S.2¾°W., 78.4 ft. with a healed blaze.

Add marks on the cap to now read: T31S

¼ S 13

S 24

R6W

2004

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Corner is located on a cut bank, 20 ft. W of the center line of BLM Rd No. 31-6-13.0, graveled surface, 12 ft. wide, bears N.20°E. and S.20°W.

From this point, a point established by Shaner in 1993 as the W-E 1/64 sec. cor. of secs. 13 & 24 (property corner), bears S.86°09'17"E., 669.64 ft. monumented with an iron rod 5/8" dia., firmly set, projecting 8" above the ground, with alum. cap, 1½" dia., affixed to top, mkd SHANER ENG RLS 430. This point was not correctly positioned and is not utilized during the course of this survey.