

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7965)

Set a sandstone 14x10x7 ins. for the 1/4 sec. cor. mkd. 1/4 on N. face, from which

A Laurel 10" dia., bears N.24°W., 40 lks. dist. mkd. 1/4 S BT

A Fir 12" dia., bears S.68°W., 25 lks. dist. mkd. 1/4 S BT.

Survey by John H. Markham, Jr. - For: Canyon Logging Co. -
Wit: D. E. Brown - June 9, 1951 - C.S. File 40/231-3

Location determined from old BT, a
Fir 15" bears S.68°W., 17.0 ft. with scribe marks, which
I remark 1/4 S BT.

At the corner point I found a stone and made a large pile of rocks, from which a

Laurel 12" dia., bears S.77°E., 7.0 ft. scribed 1/4 S BT.

A spring bears South, 5.0 ft.

Douglas Co. Surveyors Office - John Powell, Frank Jones,
Cliff Stone, crew - Sept/Oct. 1966 - C.S. File 54/31-6

Found - Mound of stones and 1" Iron pipe 1" x 24" and stone with "1/4" which has been moved.

15" now 20" D.Fir S.68°W., 17.0 ft. (to face) bark scribed.

No trace of SE Laurel BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 6 W

1/4 S 12
S 13

1966

Reblazed and rescribed:

20" D.Fir S.68°W., 17.7 ft. mkd. 1/4 S13 CS BT.

New BT - 18" Laurel N.49°E., 45.4 ft. mkd. 1/4 S12 CS BT.

Spring bears South 5.0 ft.

Found OK by Greg Lang, Oct. 1997 - M 128-18

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed Aug. 2003, - (DCSO records Vol. 54 Page(s) 21236-7)

The ¼ sec. cor. of secs. 12 & 13, perpetuated by Markham in 1951, further perpetuated by Powell in 1966,, subsequently recovered & utilized by Lang, in 1997, monumented with an iron pipe, 1¼" dia., firmly set, projecting 19" above ground, (along side of which is an iron pipe, 1" dia., firmly set projection 12" above the ground. The original sand stone, 14x10x7, mkd. ¼ has been displaced, bears S.82°W., 1.6 ft.) with brass cap (properly) mkd.

from which the remains of an original bearing tree

A sawed fir stump, 19" dia., bears S.68°W., 16.5 ft., with scribe marks ¼ CS BT visible on partially healed blaze. (Rescribed by the Douglas County Surveyors Office in 1951 and 1966)

and a bearing tree mkd. by Powell

A laurel, 20" dia., bears N.50¾°E., 45.4 ft., with no marks visible on a partially healed blaze.

and a new bearing tree

A fir, 16" dia., bears S.50½°W., 14.8 ft., mkd. ¼ S13 BT. Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

The geographic position (NAD 1983 (CORS)) of this cor. as determined by NAVSTAR Global Positioning System (GPS), utilizing dual frequency, carrier phase GPS receivers, (Trimble 5700), relative to the National Spatial Reference System, is as follows:

Latitude 42°52'59.02" N., Longitude 123°21'28.02" W.

Fd as per 2003 BLM rehab. by D. Edwards, 2/2009 - M158-67