



TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir snag 10" dia., bears S.50 3/4°W., 39 lks. dist., no marks visible. (Rec. S.49°W., 47 lks.)  
A Fir stump 40" dia., bears N.20°E., 40 lks. dist., no marks visible.  
and a bearing tree mkd. by the County Surveyor  
A Fir 24" dia., bears S.6½°E., 95½ lks. dist., with scribe marks ¼ S12 CS visible on partially opened blaze.  
Refurbish the iron post with a collar of stones, 2 ft. base to top.  
No other trees available within limits.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17308)

-----

The ¼ sec. cor. perpetuated by Powell in 1966, as described in a DCSO record, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above the ground with 1966 brass cap from which the remains of the original bearing trees:  
A Fir stump 40" dia., bears N.20°E., 40 lks. dist., no marks visible.  
A Fir snag 10" dia., bears S.50 3/4°W., 39 lks. dist., no marks visible. (Rec. S.49°W., 47 lks.)  
and the remains of a bearing tree by Powell:  
A Fir snag 25" dia., bears S.4°E., 95½ lks. dist., with healed blaze.  
and new bearing trees:  
A Fir 6" dia., bears S.34°W., 10 lks. dist., mkd. ¼ S12 BT  
A Fir 6" dia., bears N.24½°W., 40 lks. dist. mkd. ¼ S1 BT.

Found OK by G. Lang, Oct. 1997 - M 128-18  
Fd. BC & 3 BTs - D. Edwards, 2/2009 - M158-67