

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. 25 & 36; 30 & 31 T31-5.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Geo. W. Hyde under contract # 54, dated Feb. 19, 1855. (DCSO records Vol. 19, Pg. 7879)

Set post from which:

- A Fir, 20" dia. bears N.38°W., 16 lks. dist.
- A Fir, 36" dia. bears S.33°W., 26 lks. dist.
- A Fir, 20" dia. bears S.68°E., 95 lks. dist.
- A Yew, 14" dia. bears N.31°E., 64 lks. dist.

Corner set by Geo. Wenderoth, reported by B. Shaner Feb. 1964. M 27-36.

- Found- 3/4" Iron Pipe. (This Cor. found by Shaner, M27-36)
Orig. BT stump with scribes "S25" vis. bears N.38°W., 10.6 ft.
New BTs -42" D.Fir with scribes vis, N.86°W., 26.3 ft.
18" Yew BT. Orig. BT. scribes vis. bears N.31°E., 42.2 ft.
38" D.Fir with scribes visible bears S.22°W., 63.2 ft

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2078, surveyed June/Sept. 2004 (DCSO rec. Plat 31-6 2011 & Vol. 56 pg(s) 22322)

The cor. of secs. 25, 30, 31, & 36 on the E bdy. of the Tp perpetuated by Wenderoth, date unknown reported by Shaner in 1964, monumented with an iron pipe, 3/4" dia., firmly set, projecting 3" above the ground, from which the remains of the orig. BTs:

- A yew, 40" dia., bears N.31°E., 42.2 ft. with scribe marks S30 CS BT visible on a partially healed blaze. (rescribed by Wenderoth)
- A decayed fir stump, 10" dia., bears N.38°W., 10.6 ft. with the face of the blaze laying on the ground alongside the stump with scribe marks T31S R6W S25 visible.

and the remains of BTs mkd by Wenderoth

- A sawed fir stump, 48" dia., bears S.19 3/4°W., 64.6 ft. with illegible scribe marks visible on a partially healed blaze.
- A sawed fir stump, 42" dia., bears N.86°W., 27.1 ft. with no marks visible.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap marked:

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. 25 & 36; 30 & 31 T31-5.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T31S
R6W R5W
S 25 | S 30
S 36 | S 31
2004

from which

A fir, 6" dia., bears S.46½°E., 13.0 ft., mkd: T31S R5W S36 BT.

A fir, 7" dia., bears S.79¼°W., 7.4 ft., mkd: T31S R6W S36 BT.

A fir, 9" dia., bears N.15¾°W., 10.7 ft., mkd: T31S R6W S25 BT.

The iron pipe set by Wenderoth is rusted in half, top piece 18" long, bottom piece 12" long, place both halves alongside stainless steel post.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Fd per renewal record 8/2017 - R. Quimby - C.S. File 65/95-48