

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Corner Sec. 25; Sec. 30 T31-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Geo. W. Hyde under contract # 54, dated Feb. 19, 1855. (DCSO records Vol. 19 Pg. 7879)

Set 1/4 Sec. post from which:
A Vine Maple, 6" dia. bears N.54°W., 10 lks. dist.
A Vine Maple, 6" dia. bears S.89°E., 4 lks. dist.

Bruce Shaner - For Bate Lumber Co. Feb. 1964 - M 27-36

Found - No evidence of original corner.
Note - As the corner I wanted to set fell in a 6 ft. wide stream, I set no corner, but from the corner location point a:
New BTs -34" D.Fir Stump, I scribe "T31S R5W ¼ S30 BT" bears S.35°E., 11.5 ft.
36" D.Fir snag, I scribe "T31S R6W S25 ¼S BT" bears N.82°W., 38.1 ft.

Doug. County Surveyors Office - John M. Powell, Frank Jones & Joe Brady - May & June 1966, C.S. File 54/25-31

Found - 34" Fir stump S.35°E., 11.5 ft. scribed T31S R5W ¼ S30 BT.
36" Fir snag N.82°W., 38.1 ft. scribed T31S R5W ¼ S25 BT.

As noted earlier, corner falls in creek, therefore no corner was set.

Set - Brass Cap for witness corner marked:
COUNTY SURVEYORS OFFICE
R T31S R
6 W.C. 25' N. to 5
W ¼ S25|S30 W
1966

New BTs- 40" Fir stump S.40°E., 12.3 ft. scribed W.C. ¼ S30 CS BT.

7" Alder S.80°W., 19.0 ft. scribed W.C. ¼ S25 CS BT.
Brass Cap lies about 25.0 ft. south of stream and 28.6 ft. west of spring branch.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2078, surveyed June/Sept. 2004 (DCSO rec. Plat 31-6 2011 & Vol. 56 pg(s) 22322)

The ¼ sec. cor. of secs. 25 & 30, on the E bdy of the Tps. reestablished by Shaner in 1964 and is accepted as the corner, perpetuated by Powell in 1966 from which the remains of BTs mkd by Shaner continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Corner Sec. 25; Sec. 30 T31-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir stump, 28" dia., bears S.50°E., 11.5 ft. with fragmentary scribe marks visible on a partially healed blaze.

A fir snag, 41" dia., bears N.81½°W., 38.1 ft. with scribe marks T31S R6W S25 BT visible on an open blaze. and a witness cor. mkd by Powell

An iron pipe 1¼" dia., loosely set, projecting 24" above the ground for a witness corner, bears S.1°34'05"E., 23.85 ft. with brass cap mkd: COUNTY SURVEYORS OFFICE WC T31S R6W 25 FT N TO S25 S30 R5W ¼ 1966 (Rec. cor. call is ambiguous)

An alder, 9" dia., bears S.34½°W., 32.0 ft. with a healed blaze.

At the corner point

Set an iron rod, 30" long, 5/8" dia., 28" in the ground, with alum. cap 1½" dia., affixed to top, mkd:

T31S
R6W ¼ R5W
S 25|S 30
2004

from which

A fir, 20" dia., bears N.27¼°E., 52.8 ft., mkd: ¼ S30 BT.

A fir, 19" dia., bears N.29¾°W., 29.3 ft., mkd: ¼ S25 BT.

Corner is located in the center of a creek 10 ft. wide, course N.45°E.