

TOWNSHIP 31 RANGE 6 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Geo. W. Hyde under contract #54, dated Feb. 19, 1855. (DCSO records Vol. 19, Pg. 7878)

Set ¼ sec. post from which:
A Chinquapin, 10" dia., bears N.25°W., 39 lks.
A Fir, 6" dia., bears N.71°E., 39 lks.

BLM dependent resurvey by Daniel E. Weller, Cadastral Surveyor, under Group #1884, surveyed July/Sept 1998. (DCSO records Vol. 53 Page(s) 20470)

Point for the ¼ sec. cor. of sec. 13 only, T31S, R6W, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 23" in the ground, and brass cap mkd.

T 31 S
R 6 W | R 5 W
1/4 |
S 13 |
1998

from which
A fir, 8" dia., bears S.17½°W., 28 lks., mkd. 1/4 S13 BT.
A fir, 11" dia. bears N.54¼°W., 61½ lks., mkd. 1/4 S13 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.