

PRIMARY CORNER DESCRIPTION Sec. Cor. 12 & 13 (East), Only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Pages 7877-78)

Set post for corner from which:

- A Chinquapin, 8" dia. bears N.52°W., 137 lks. dist.
- A Fir, 18" dia. bears S.48°W., 26 lks. dist.
- A Fir, 18" dia. bears N.64°E., 30 lks. dist.
- A Yew, 14" dia. bears S.42°E., 52 lks. dist.

Resurvey of North 2 miles of the West Bdy., T31S R5W by Wm. P. Wright under Contract #281 dated May 16, 1878 (DCSO Records, Vol. 19 Page 13667)

Near the top of mountain. Still not finding fir post or evidence of post. Reestablish the same by setting a post 5" x 5" dia., by 4 ft. long, 20" in ground for corner to secs. 7, 18, 12 and 13, from which

- A Chinquapin 4" dia., bears S.80°W., 10 lks.
- A Red Fir 30" dia., bears N.60°E., 40 lks.
- A Laurel 12" dia., bears S.65°E., 46 lks.
- A Maple 2" dia., bears S.16°W., 28 lks.

B.L.M. Resurvey - John M. Jelley, Lynn M Roseberry, Floyd A Brooks, under Group #s 320 & 614, surveyed, June 1966 through May 1968. (DCSO records Vol. 35, Pg.14377)

Found, Original bearing tree -

- A Fir, 58" dia. bears N.60°E., 40 lks. dist. with scribe marks S7 BT visible on opened blaze.

Set - An iron post, 28" long, 2½" dia. 22" in ground with

brass cap marked: T 31 S
 R 6 W R 5 W
 S 12 S 7
 S 13 S 18
 1966

from which new bearing trees

- A Fir, 15" dia. bears S.25°E., 87½ lks. dist. marked:
T31S R5W S18 BT
- A Fir, 20" dia. bears S.53½°W., 164 lks. dist. marked:
T31S R6W S13 BT
- A Fir, 19" dia. bears N.7°W., 75 lks. dist. marked:
T31S R6W S12 BT

Greg Lang, for Silver Butte Timber Co. Oct. 1997 - M128-18

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. 12 & 13 (East), Only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Monumented Section corner from original evidence.
Found -Original Fir stump with bottom of face showing.
Bears S.46°W., 17.16 ft. (1855 corner)
Original uprooted Yew, bears S.39°E., 34.3 ft.
Stump of orig. line tree bears S.0°18'41"W., 61.11 ft. (rec. 62.7)
Original uprooted Fir to NE.
No sign of orig. Chinquapin.
Set - 5/8" iron rod, with plastic cap marked "Lang Surveying"
New Accessories -
Spike in face of 8" Fir bears, S.78°57'W., 30.45 ft. scribed "T31S R6W S13" "BT"
Spike in face of 11" Fir bears, N.45°26'W., 21.62 ft. scribed "T31S R6W S12" "BT"
Spike in face of 9" Fir bears, N.2°13'E., 7.25 ft. scribed "T31S R5W S18" "BT"
Spike in face of 16" Hemlock bears S.55°13'E., 9.63 ft. scribed "T31S R5W S18" "BT"
Note - 1966 BLM Corner bears N.10°15'14"W., 403.57ft.

BLM dependent resurvey by Daniel E. Weller, Cadastral Surveyor, under Group #1884, surveyed July/Sept 1998. (DCSO records Vol. 53 Page(s) 20471-2)

The cor. of secs. 12 & 13 only, T31S R6W, perpetuated by Lang, in 1998, monumented with an iron rod, 5/8" diam., firmly set, projecting 9" above ground, with plastic cap mkd. LANG SURVEYING, from which the remains of the original bearing trees:

- A roothole, bears N.64°E., 30 lks.
 - A rotted fir stump, 26" diam., bears S.48°W., 26 lks., with no marks visible.
- and bearing trees mkd. by Lang
- A hemlock, 9" diam., bears N.4¼°E., 11½ lks., with scribe marks T31S R5W S18 BT visible on partially healed double blaze.
 - A hemlock, 16" diam., bears S.55½°E., 16 lks., with scribe marks T31S R5W S18 BT visible on partially healed double blaze.
 - A fir, 8" diam., bears S.79¼°W., 47 lks., with scribe marks T31S R5W S13 BT visible on partially healed double blaze.
 - A hemlock, 12" diam., bears N.45°W., 33½ lks., with scribe marks T31S R5W S12 BT visible on partially healed double blaze.

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. 12 & 13 (East), Only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 8" in the ground, with metal fence post alongside, supported in a mound of stone, 2 ft. base, to top, and brass cap mkd.

T 31 S
R 6 W R 5 W
S 12 | S 18
S 13 |
1998

Deposit a magnet in a white plastic case at the base of the stainless steel post and remove the iron rod.

From this point, a fir stump, 32" diam., reported by Lang as a line tree, bears South, 0.925 chs., with no marks visible. Lang also did not find any marks, so this point is not utilized in this survey.