

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 12 (East) only.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Page 7877)

Set 1/4 sec. post from which:
A Fir, 6" dia. bears N.66½°E., 38 lks. dist.
A Fir, 8" dia. bears S.48°W., 13 lks. dist.

Wm. P Wright, Dep. Surveyor, June 27, 1878. - Resurvey of north 2 miles of the west boundary, T31S R5W. under Contract #281 dated May 16, 1878 (DCSO records Vol. 33, Pg. 13667).

Still finding, after strict search, no evidence of ¼ post. Reestablished the same by setting post 4" x 4" X 3½ ft. long 20" in ground from which:
A Madronna, 5" dia. bears S.13°W., 31 lks. dist.
A Madronna, 5" dia. bears S.33°E., 80 lks. dist.

James W. Byron, County Surveyor, John Powell & crew. Aug. 1966 - C.S. File 54/25-15

Found - Original 6" Fir S.48°W., 8.6 ft., now remains of old Fir, shows old axe work. No scribing found. See statement signed by James Combs in file, to wit: "I, James Combs, state that the remains of old Fir stump found and used on this date for the Original SE BT did show good wood scribing in 1952".

Found - Base of Original NE BT, no scribing.
Tag set by Haines on now down 30" Fir, see forest appraisal record.

Set - Brass Cap at 1/4 Corner marked: COUNTY SURVEYORS OFFICE
R T31S R
6 S 12 | S 7 5
W ¼ W
1966

New BTs -
22" D.Fir, S.28°W., 68.2 ft. scribed "¼ S12 CS BT"
10" Yew, S.59°E., 26.4 ft. scribed "¼ S7 CS BT"

Greg Lang for Silver Butte Timber Co. Oct. 1997 - M 128-18

It appears this corner has been subsequently destroyed with the exception of a Fir stump in the SW quadrant.

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 12 (East) only.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Daniel E. Weller, Cadastral Surveyor, under Group #1884, surveyed July/Sept 1998. (DCSO records Vol. 53 Page(s) 20472-3)

The ¼ sec. cor. of sec. 12 only, T31S R6W, perpetuated by Byron,, in 1966, recovered by Lang, in 1998; monumented with an iron pipe, 1½" diam., firmly set, projecting 14" above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

 R T31S R
 1/4 6 5
 W S12
 1966

from which the remains of a bearing tree mkd. by Byron
 A fir stump, 30" dia., bears S.29°W., 100½ lks., with a
 healed blaze.
and new bearing trees
 A fir, 12" dia., bears S.19 3/4°W., 16½ lks. mkd. ¼ S12 BT
 A fir, 10" dia., bears N.24½°W., 57½ lks., mkd. ¼ S12 BT.

David Edwards - For: Seneca Jones Timber Co. & Sliver Butte
Timber Co. - 2/2009 - M158-67

Found - Brass cap
 13" Fir, S.19¾°W., 10.9' with healed blaze.
New BT - 10" Fir bears N.35°W., 35.4 ft.