

PRIMARY CORNER DESCRIPTION AP (Line Tree sec. 1 & sec. 6 of T31-5)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Orig. GLO Survey - Geo. W. Hyde, Deputy Surveyor under contract # 54, dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7877)

Set - Fir, 20" dia., at 62.50 chs

FD. OK - Douglas County Surveyors - Oct. 1979 - RM 3-26

Douglas County Surveyors Office - Randall Smith & Stephen Flause - Feb. 25, 1997 - C.S. 64/74-7

Found - 20" now 34" dia. 30' high D.Fir snag, with 5 axle marks in bark on north trunk, 2 axe marks in bark on south trunk and a previously opened axing no marks visible. (orig., 1855 south line tree).
Hub and tack per 1979 DCSO traverse tie to line tree record "S20°28'38"W., 116.06' GRID" confirms tree to be line tree tied by DCSO in 1979. South line tree between sec. 1 and 6.

Set - 2 3/8" dia. Brass cap on a 1 3/8" by 32" long iron pipe protrudes 4" above ground. Bears south 5' from line tree.

10" dia. D.Fir, double blazed and scribed "SLT S1 CS BT", bears S.57°W., 16.5".

7" dia. Pine, double blazed and scribed "SLT S1 CS BT", bears S.20°W., 30.9'.

8" dia. D.Fir, double blazed and scribed "SLT S6 CS BT", bears N.33°E., 24.9'.

BLM dependent resurvey by Daniel E. Weller, Cadastral Surveyor, under Group #1884, surveyed July/Sept 1998. (DCSO records Vol. 53 Page(s) 20475-6)

An original line tree, a fir snag, 34", with five notches on N. & two notches S. side, recovered by Douglas County Surveyor, in 1979, perpetuated by Douglas County Surveyors Office, in 1997. This now becomes an Angle Point, from which a reference monument and bearing trees by Douglas County Surveyors Office:

An iron pipe, 1½", firmly set, projecting 4" above ground, bears south, 7½ lks., with brass cap mkd. DOUGLAS COUNTY SURVEYORS OFFICE B01 SLT BEARS NORTH 5 FT 1997.

A fir, 8", bears N.33°E., 38 lks., with scribe marks SLT S6 CS BT visible on partially healed double blaze.

A fir, 7", bears S.20°W., 46 lks., with scribe marks SLT S1 CS BT visible on partially healed double blaze.

A fir, 10", bears S.57°W., 22 lks., with scribe marks SLT S1 CS BT visible on partially healed double blaze.