

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (Tsp. Cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8712) and Vol. 19 Page 8029)

Set a Live Oak post 4½ ft. long, 4" sq., 22" in the ground for the corner to Township 31, and 32 South, Ranges 7 and 8 West, marked T31S R7W S31 on NE. face; T32S R7W S6 on SE. face; T32S R8W S1 on SW. face; T31S R8W S36 on NW. face; and six notches on each angle of same, from which

A Fir 24" dia., bears N.42°E., 40 lks. dist., mkd. T31S R7W S31 BT.

A Live Oak 8" dia., bears S.78°E., 61 lks. dist., mkd. T32S R7W S6 BT.

A Live Oak 8" dia., bears S.45°W., 40 lks. dist., mkd. T32S R8W S1 BT.

A Fir 12" dia., bears N.38°W., 97 lks. dist., mkd. T31S R8W S36 BT.

Fd. and used by Byars in GLO survey, Contract #456, dated July 28, 1882 (DCSO records, Vol. 19 Page 8097)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Cliff Stone, crew - Dec. 1, 1966 - C.S. File 54/36-64

Found - 8" now 13" Live Oak S.78°E., 40.3 ft., opened for scribe.

12" D.Fir, now rotten stob, N.45°W., 64.0 ft. (Rec. N.38°W.)

No trace of NE or SW bearing trees.

Set Brass cap at township corner mkd: County Surveyors Office

		T 31 S	
R8W	S 36		S 31
	S 1		S 6
		T 32 S	R7W
		1966	

New BTs -10" D.Fir S.72°W., 33.6 ft. mkd. T32S R8W S1 CS BT.

12" D.Fir S.48½°E., 24.4 ft. mkd. T32S R7W S6 CS BT

8" Live Oak N.53°E., 46.6 ft. mkd. T31S R7W S31 CS BT

6" Live Oak N.48°W., 4.6 ft. mkd. S36 CS BT.

This corner lies about 33.0 ft. E. of creek on steep W. slope.

Cor. Fd. and used in BLM survey by Jelley and Carlson, Group #899, surveyed Aug. 1976/Nov. 1977 (DCSO records, Vol. 41 Pages 16182-83)

Fd. OK, Aug. 1981 by H. Johnstone - M 88-62

cont.

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (Tsp. Cor.)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Ron Quimby - 10/2013 - C.S. File 65/80-26

Found - 1966 DCSO brass cap (properly mkd)
8" live oak N.49°E., 46.2 ft., vis. scribes
22" fir S.48°E., 24.4 ft., healed face.
15" fir S.69°W., 32.3 ft., healed face.
8" live oak N.41°W., 4.6 ft. vis. scribes
New - Set alum. post 2' south & east.
Re-tag trees.
Note - Area burnt 7/2013

BLM resurvey by Brandon G Courtright, Cadastral Surveyors,
under Group No. 2754, surveyed May/July 2014 - (DCSO records,
Vol. 58 page(s) 23366-7)

The cor. of Tps. 31 & 32 S., Rs. 7 & 8 W., perpetuated by
Powell, Deputy Douglas County Surveyor in 1966, monumented
with an iron post, 1½" dia., firmly set, projecting 19" above
ground, with brass cap (properly) mkd.
from which the remains of an original bearing tree, reported
by Jelley and Carlson in 1976-77

A live oak snag, 12" dia., bears S.78¾°E., 39.3 ft., no
marks visible in a hollowed and charred blaze.
(Record, S.78°E., 40.3 ft.)

and the BTs mkd. by Powell, reported by Jelley and Carlson

A live oak, 7" dia., bears N.48°E., 44.7 ft., with a
healed blaze. (Record, N.49°E., 46.2 ft.)

A fir, 20" dia., bears S.48½°E., 24.4 ft., with a healed
double blaze.

A fir, 13" dia., bears S.69°W., 32.3 ft., with a healed
double blaze.

A double live oak, 9" dia., bears N.41°W., 4.6 ft., with
a healed blaze.

The geographic position in NAD 1983 (2011)

Latitude: 42°49'29.98" N. Longitude: 123°35'03.65" W.