

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24 of T31-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Pages 8031-32)

-----  
Set a Laurel post 4 ft. long, 4" sq., 24" in the ground marked T31S R7W S18 on NE. face; S19 on SE. face; S24 on SW.; and R8W S13 on NW. face, for the cor. to secs. 13, 18, 19 and 24, from which

- A Laurel 7" dia., bears N.65°E., 41 lks. dist. mkd. T31S R7W S18 BT.
- A Laurel 7" dia., bears S.68°E., 35 lks. dist. mkd. T31S R7W S19 BT.
- A Laurel 7" dia., bears S.42°W., 30 lks. dist. mkd. T31S R8W S24 BT.
- A Laurel 7" dia., bears N.85°W., 24 lks. dist. mkd. T31S R8W S13 BT.

Looked for, not fd, by DCSO crew - July 1969 - C.S. 54/36-21

Survey by Dennis A. Crowe - For: U.S. Plywood - Jan. 1973 - C.S. File 55/279 and M 47-60

-----  
A diligent search was made yielding no acceptable evidence of adequate corner monumentation.

Set 36" aluminum cap, iron pipe, 24" into the ground, from which

- 8" P. Pine scribed on the wood, bears S.23°E., 21.5 ft.
  - 8" Fir scribed on the wood, bears N.62°E., 19.5 ft.
- No other acceptable accessories available.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - March 8, 1977 - M 65-5

-----  
Found 1972 Alum. cap and 3 BTs, N.6°10'11"E., 47.37 ft. from true section corner.

- Set 5/8"x30" Iron rod & alum. cap for sec. corner, from which
- 5" Fir bears S.82°E., 19.3 ft.
  - 5" Madrone bears S.65½°W., 5.1 ft.
  - 4" Madrone bears N.60°W., 3.3 ft.
  - 9" Pine bears N.24°E., 30.8 ft.

BLM Resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors, under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO records Vol. 41 Page(s) 16193-94)

-----  
The Sec. cor., reestablished at proportionate distance and recorded by Johnstone, in 1977, and is accepted as the best available evidence of the position of the original corner,  
(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T31-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

monumented with an iron rod, 5/8" dia., firmly set, projecting 8" above ground, with 1977 alum. cap.

from which bearing trees mkd. by Johnstone:

- A Pine 9" dia., bears N.24°E., 46½ lks. dist., with fragmentary scribe marks visible on open blaze.
- A Fir 5" dia., bears S.82°E., 29 lks. dist., with fragmentary scribe marks visible on open blaze.
- A Madrone 5" dia., bears S.65½°W., 7½ lks. dist., with fragmentary scribe marks visible on open blaze.
- A Madrone 4" dia., bears N.60°W., 5 lks. dist., with fragmentary scribe marks visible on open blaze.

From this point, a cor. established by Dennis Crowe in 1972, bears S.4°24'W., 0.72 chs. dist., monumented with an iron post, 1½" dia., firmly set, projecting 8" above round, with 1972 alum. cap,

from which bearing trees mkd. by Crowe:

- A Fir 10" dia., bears N.70°E., 29 lks. dist., with healed blaze.
- A Pine 10" dia., bears S.22°E., 31 lks. dis., with healed blaze.