

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Pages 8032-33)

Set a Pine post 4 ft. long, 4" sq., 2 ft. in the ground, marked T31S R7W S7 on NE. face; S18 on SE. face; S13 on SW. face, and R8W S12 on NW. face; also four notches on S. and two notches on N. angles of the same for the cor. to secs. 7, 12, 13 and 18, from which

A Pine 8" dia., bears S.15°E., 160 lks. dist. mkd. T31S R7W S18 BT.

A Pine 16" dia., bears S.60°W., 134 lks. dist. mkd. T31S R8W S13 BT.

A Pine 16" dia., bears N.31°W., 80 lks. dist. mkd. T31S R8W S12 BT.

No tree convenient in sec. 7.
Raised mound stone along side.

G.R. Lecklider - For: C & D Lumber Co. - June 1962 (typed 3/2011) - M23-68

Found - 28" Pine, S.15°E., 160 lks. (scribe vis.)
26" Pine, S.60°W., 134 lks. (catface)
38" Pine, N.31°W., 80 lks. (scribe vis.)

Douglas Co. Surveyors Office-79 - John M. Powell, and crew - Oct. 1966 - C.S. File 54/36

Found - 3/4" I.Pipe at corner. (probably set by Lecklider on his map M 23-68)
16" now 36" Pine, N.31°W., 55.4 ft., shows scar.
8" Pine now (?), S.16°E., 105.6 ft., shows scar.
16" now 26" Pine, S.60°W., 88.4 ft. tree had been opened scribing visible "R8".

Set Brass cap at cor. mkd: County Surveyors Office

R	T 31 S	R
8	S 12 S 7	7
W	S 13 S 18	W

1966

New BTs -13" D.Fir N.44°W., 25.6 ft. mkd. T31S R8W S12 CS BT
15" Pine S.7°W., 19.9 ft. mkd. T31S R8W S13 CS BT.
10" Pine S.37°E., 20.1 ft. mkd. T31S R7W S18 CS BT.
7" D.Fir N.21°E., 33.2 ft. mkd. T31S R7W S7 CS BT.

continued next page

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Quimby - Ryan Palmer, Party chief - 3/2011 - C.S. 65/72-9

Condition Report only

Found - DCSO BC (properly marked)

36" Pine stump N.31°W., 55.4 ft.

30" Pine S.16°E., 105.6 ft. good scar.

30" Pine S.60°W., 88.4 ft. good scar.

20" Fir N.44°W., 25.6 ft. good scar.

24" Pine S.7°W., 19.9 ft. good scar.

20" Pine S.37°E., 20.1 ft. good scar.

16" D.Fir N.21°E., 33.2 ft. good scar.

Note - Corner is in flat area approx. 150' NE of road.

Fd. as per rec. by D. Edwards - Nov. 2017 - M173-76 - set 6'
steel post 2 ft north.