

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; and 1 of T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8034)

Set a Laurel post, 3 ft. long, 3" sq., 20" in the ground, marked $\frac{1}{4}$ S. on the W. side for the $\frac{1}{4}$ sec.cor., from which
A Laurel 12" dia., bears N.74°E., 21 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Fir 22" dia., N.87°W., 56 lks. dist. mkd. $\frac{1}{4}$ S BT.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under under Special Instructions dated March 1, 1917 - (DCSO records Vol. 19 Page(s) 8083-84) and (duplicated info. in Vol. 27 Pg. 11631)

Point for the old $\frac{1}{4}$ sec.cor., located by reference to the bearing trees. The NW. tree fallen.
At the exact cor. point,
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked:
 $\frac{1}{4}$
S 1 | S 6
1918
from which
A Yellow Pine 50" dia., bears S.52°E., 39 lks. dist. mkd. $\frac{1}{4}$ S6 BT. (Old BT)
A Fir 40" dia., bears N.33°W., 49 lks. dist. mkd. $\frac{1}{4}$ S1 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - 1972 - C.S. File 54/36

Found - 1918 govt. brass cap under large Fir windfall.
40" Pine S.52°E., 39 lks., shows scribe.
44" Fir N.33°W., 49 lks., shows scar.
This corner found by Don E. Garrett, July 1972. See note in C.S. File 54/36-188