

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8077)

Marked a W.Oak 7" dia., ¼ S. on N. side for the ¼ sec.cor., from which

A W.Oak 4" dia., bears S.8°W., 16 lks. dist. mkd. ¼ S BT.

A W.Oak 4" dia., bears N.10°W., 26 lks. dist. mkd. ¼ S BT.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - March 8, 1977 - M 65-5

Set brass cap in concrete monument, from which

15" Fir S.81°E., 52.2 ft.

7" Oak N.59°E., 79.4 ft.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Oct. 26, 1992 - C.S. File 64/32-12

Found - 2" dia. 1977 brass cap set in concrete on road cut bank.

18" now 18" dia. dead D.Fir with a partially healed single blaze, scribing visible "¼ BT" bears S.81°E., 54.0 ft. (Rec. S.81°E., 52.2 ft.)

7" now 8" dia. W.Oak with a partially healed rotted single blaze, scribing visible "¼ BT" bears N.59°E., 79.4 ft. (agrees w/rec)

New BTs- 17" dia. Madrone double blazed and scribed "¼ S18 CS BT" bears N.89½°E., 66.6 ft.

9" dia. D.Fir double blazed and scribed "¼ S19 CS BT" bears S.59½°W., 81.5 ft.

Corner lies approx. 12 ft. East of road.