TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8081-82)

Set an Oak post 3 ft. long, 4" sq., 18" in the ground, marked ¼ S. on the N. side for the ¼ sec. cor., from which

A Laurel 6" dia., bears N.85°E., 43 lks. dist. mkd. ¼ S BT.

A Live Oak 8" dia., bears S.28°W., 15 lks. dist. mkd. ¼ S BT.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under under Special Instructions dated March 1, 1917 - (DCSO records Vol. 19 Page(s) 8090) and duplicated info. in Vol. 27 Pg. 11636)

The ¼ sec. cor., located by reference to the bearing trees. At the exact cor. point

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor., with brass cap mkd: ¼ S 6 / S 7 / 1918

from which

A Live Oak 8" dia., bears N.80°E., 57 lks. dist. mkd. ¼ S6 BT. (New BT)

A Live Oak 8" dia., bears S.28°W., 15 lks. dist. mkd. ¼ S7 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - June 23, 1969 - C.S. File 54/36-85

Found - 1918 GLO brass cap, properly set and marked.
8" now 12" Live Oak S.28°W., 9.9 ft., shows good scar.
No trace of SW. bearing tree.

New BT - 6" D.Fir N.63°E., 21.8 ft. mkd. ¼ S6 CS BT.