

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & 6 of T30-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William H. Byars, Deputy Surveyor, under Contract #448, dated June 13, 1882 - (DCSO Records, Vol. 17 Pg. 7248)

Set a Maple post 3 ft. long, 3" sq., 18" in the ground mkd. $\frac{1}{4}$ S on N. side for the $\frac{1}{4}$ sec. cor., from which
An Alder 14" dia., bears N.25°E., 21 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Maple 12" dia., bears S.58°E., 27 lks. dist. mkd. $\frac{1}{4}$ S BT

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Page(s) 7290) and duplicated info. in Vol. 27 Pgs. 11613-14)

The old $\frac{1}{4}$ sec. cor., located by reference to the bearing trees. At the exact corner point
St an Iron post 3 ft. long, 1" dia., 26" in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ $\frac{S\ 31}{S\ 6}$
1918

from which
A Fir 18" dia., bears N.60°E., 76 lks. dist. mkd. $\frac{1}{4}$ S31 BT. (New BT)
A Fir 8" dia., bears S.41°W., 31 lks. dist. mkd. $\frac{1}{4}$ S6 BT. (New BT)
An Alder 24" dia., bears N.25°E., 13 lks. dist. mkd. $\frac{1}{4}$ S31 BT. (Old BT)
A Maple 16" dia., bears S.48°E., 28 lks. dist. mkd. $\frac{1}{4}$ S6 BT. (Old BT)

Survey by Howard Johnstone - For: Roseburg Lumber Co. - Feb. 10, 1983 - M 93-55

Found - 1918 GLO brass cap and iron pipe.
24" W.Fir N.60°E., 50.2 ft.
20" W.Fir S.41°W., 20.5 ft.
New BTs -5" Yewwood, S.62°E., 22.7 ft.
10" W.Fir N.46°E., 22.8 ft.