

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8075)

-----  
Set a Fir post, 3 ft. long, 3" sq., 18" in the ground, mkd.  $\frac{1}{4}$  S. for the  $\frac{1}{4}$  sec. cor., from which

A Fir 9" dia., bears N.45°E., 6 lks. dist. mkd.  $\frac{1}{4}$  S BT.

A Fir 14" dia., bears N.50°W., 44 lks. dist. mkd.  $\frac{1}{4}$  S BT.

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - March 18, 1970 - C.S. File 54/36-16

-----  
Found - 9" now 13" D.Fir N.45°E., 4.0 ft. shows good scar.  
14" now 27" D.Fir N.50°W., 29.0 ft., shows bark scribe " $\frac{1}{4}$  S".

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 7 W  
 $\frac{1}{4}$  S 19 | S 20  
1970

Reblazed and rescribed:  
27" D.Fir N.50°W., 29.0 ft. scribed " $\frac{1}{4}$  S19 CS BT"