

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8075-76)

Set a Yew post, 4 ft. long, 4" sq., 22" in the ground, mkd. T31S R7W S17 on the NE. face; S20 on SE. face; S19 on the SW. face; and S18 on the NW. face. Also 3 notches on the S. and 5 notches on the E. angles of same, for the cor. to secs. 17, 18, 19 and 20, from which

- A Fir 15" dia., bears N.62°E., 40 lks. dist. mkd. T31S R7W S17 BT.
- A Fir 12" dia., bears S.68°E., 8 lks. dist. mkd. T31S R7W S20 BT.
- A Fir 26" dia., bears S.24°W., 8 lks. dist. mkd. T31S R7W S19 BT.
- A Fir 36" dia., bears N.78°W., 51 lks. dist. mkd. T31S R7W S18 BT.

Survey by G. Robert Lecklider, - For: C & D Lumber Co. - June 1962 - M 23-68

Found 3 bark scribed BTs. BTs did not fit orig. govt. field notes, so I Set a post at intersection of faces, from which
36" Fir S.26°W., 5.0 ft. (rescribed)
14" Fir S.75°E., 15.7 ft.
28" Fir N.65°E., 26.8 ft.
10" Fir N.10°E., 14.0 ft. (New BT)

Douglas Co. Surveyors Office - John M. Powell, Willie Penley, crew - June 22, 1970 - C.S. File 54/36-27

Found - Orig. 15" now 30" D.Fir N.62°E., 26.4 ft., rescribed "S17 RE 4079 BT"
Orig. 12" now 14" D.Fir S.68°E., 5.3 ft. rescribed "S20 RE 4079 BT"
Orig. 26" now 33" D.Fir S.24°W., 5.3 ft. rescribed "S19 RE 4079 BT", some orig. scribe marks visible.
10" D.Fir N.3°E., 14.0 ft. (Rec. N.10°E., 14.0 ft.) shows pitched over scribing. (1962 BT)

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 7 W
S 18 | S 17
S 19 | S 20
1970

New BT - 10" D.Fir N.66°W., 9.9 ft. scribed T31S R7W S18 CS BT.