TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 19 Page(s) 8021-22)

Set ¼ sec. post, from which
A W.Oak 5" dia., bears S.10°E., 28 lks.
A W.Oak 5" dia., bears S.75°W., 55 lks.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under under Special Instructions dated March 1, 1917 - (DCSO records Vol. 19 Page(s) 8093-94) and duplicated info. in Vol. 27 Pg. 11639)

The old ¼ sec. cor., located by reference to the bearing trees. At the exact cor. point
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor., with brass cap mkd: ¼
S 6|S 5
1918
from which
A W.Oak 10" dia., bears S.11°E., 28 lks. dist. mkd. ¼ S5 BT. (Old BT)
A W.Oak 10" dia., bears S.83°W., 54 lks. dist. mkd. ¼ S6 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - June 20, 1969 - C.S. File 54/36-12

Found - 10" W.Oak now 14", S.83°W., 35.6 ft. Tree opened, scribe marks visible, not legible, rotting face.
10" W.Oak now 12", S.11°E., 18.5 ft., shows good scar.
1918 GLO brass cap at corner.
New BT - 16" Cedar S.79°W., 21.5 ft. scribed ¼ S6 CS BT.
All trees tagged.

Fd. OK, Feb. 1983 by H. Johnstone - M 93-55