

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8071)

Set a Pine post 3 ft. long, 4" sq., 18" in the ground, marked 1/4 S on N. side for the 1/4 sec. cor., from which
A Pine 28" dia., bears S.40°E., 11 lks. mkd. 1/4 S BT
A Laurel 15" dia., bears N.23°W., 27 lks. mkd. 1/4 S BT.

BLM resurvey by Donald Beck, Cad Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO rec Vol 33 Pg 13641)

The 1/4 sec. cor., determined at record bearing and distance from the remains of the original bearing trees:

A Madrone 20" dia., bears N.23°W., 27 lks. mkd. 1/4 S on open blaze.

A rotted Pine stump 30" dia., bears S.40°E., 11 lks. with no marks remaining.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 21" in the ground, with brass cap mkd:

1/4 S 29
S 32

T 31 S R 7 W

1963

from which new bearing trees

A Fir 6" dia., bears N.30 1/2°E., 25 lks. mkd. 1/4 S29 BT

A Fir 8" dia., bears S.10 1/2°W., 19 1/2 lks. mkd. 1/4 S32 BT.

Fd. and used in BLM resurvey by Jelley and Rogers, Cadastral Surveyors - under Group #1086 - surveyed April/June 1982 - (DCSO records, Vol. 46 Pages 17554-55)

Greg Lang - Trevor Lang, Party Chief - J. Herzberg, Witness - October 2005 - C.S. File 65/54-39

Found - Brass Cap set by BLM

A 31" Laurel bears N.24°W., 18.82 ft (orig rec is N.23°W., 17.82 ft)

A Pine stump bears S.34 1/2°E., 8.25 ft (orig rec is S.40°E., 7.26 ft)

A 20 1/2" Fir bears N.27 1/2°E., 16.50 ft (1964 BLM rec is N.30 1/2°E 16.5 ft)

A 16" Fir bears S.11 1/2°W 12.87 ft (1964 BLM rec is S.10 1/2°W., 12.87 ft)

New - A 19" Fir bears S.88°W., 24.60 ft scribed "1/4 S32 BT"
continued next page

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Note - We set spikes in the base of all existing & new
BTs for measuring distances to the corner;
bearings to the trees were measured with a total
station & are based on the 1964 resurvey of the
north line of Section 32)
Corner lies on the NW'ly side of a ridge about 150'
west of a road.