

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8076)

Marked a Live Oak 7" dia., 1/4 S. on N. side for the 1/4 sec. cor., from which

A Fir 14" dia., bears S.32°W., 6 lks. mkd. 1/4 S BT.

A Live Oak 7" dia., bears N.42°E., 16 lks. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, W. Penley, crew - June 22, 1970 - C.S. File 54/36-28

Found - 7" Live Oak Corner Tree, now 7", shows good scar on North face.

14" now 14" D.Fir S.32°W., 4.0 ft., shows old face and faint bark scribe.

7" Live Oak now 6", N.42°E., 10.6 ft., tree opened, rotted face, some scribe marks visible, but not legible.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 7 W

1/4 S 17
S 20
1970

Set on northerly side of cor. tree.

New BT - 18" D.Fir N.68°E., 26.0 ft. mkd. "1/4 S17 CS BT"

Reblazed and rescribed:

14" D.Fir S.32°W., 4.0 ft. scribed "1/4 S20 CS BT"

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell, Randy Smith, crew - Feb. 3, 1983 - C.S. File 62/7-14

Found - Orig. 7" now 7" Live Oak corner tree with good scar on North side. Brass cap set in 1970 by DCSO no longer in ground.

Orig. 14" Fir now 14" with partially healed pitched over blaze bears S.32°W., 4.0 ft.

Orig. 7" Live Oak now 7" with previously opened now rotted face with no scribing visible, bears N.42°E., 10.6 ft.

18" Fir now 19" with partially healed pitched over blaze bears N.68°E., 26.0 ft.

New Accessories:

7" Fir scribed "1/4 S17 CS BT" in double blaze bears N.85°W., 23.4 ft.

8" Live Oak scribed "1/4 S20 CS BT" in double blaze bears S.64°E., 20.4 ft.

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

5/8" x 30" Iron rod with alum. cap mkd. "Douglas Co.
Surveyor BO 1" bears N.43°W., 10.0 ft.
5/8" x 30" Iron rod with alum. cap mkd. "Douglas Co.
Surveyor BO 2" bears S.55°W., 12.0 ft.
Line crossing tag on 20" ± Fir N.22°E., 200 ft. ±.
Sketch in C.S. file.