

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 19 Page(s) 8022)

Set ¼ sec. post, from which
A B.Oak 14" dia., bears N.20°E., 50 lks.
A B.Oak 10" dia., bears S.45°E., 47 lks.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under under Special Instructions dated March 1, 1917 - (DCSO records Vol. 19 Page(s) 8088-89) and duplicated info. in Vol. 27 Pg. 11635)

Point for old ¼ sec. cor., located by reference to the bearing trees. At the exact cor. point,
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor., with brass cap mkd: ¼ $\frac{S\ 5}{S\ 8}$
1918

from which
A B.Oak 18" dia., bears N.22°E., 51 lks. dist. mkd. ¼ S5
BT. (Old BT)
A B.Oak 15" dia., bears S.31°E., 45 lks. dist. mkd. ¼ S8
BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - June 19, 1969 - C.S. File 54/36-10

Found - 18" B.Oak now 23", N.22°E., 33.7 ft., has rotten face.
15" B.Oak, now down and rotten face, S.31°E., 29.7 ft. Found fragments of scribing.
Also found 1918 GLO brass cap at corner.
New BTs -14" D.Fir N.15°W., 18.3 ft.
20" D.Fir S.60°W., 13.2 ft. scribed ¼ S8 CS BT.
This corner lies in very old E-W fence line.

Fd. OK, March 22, 1985 by H. Johnstone - M 98-45