

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 242700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T30-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Page(s) 7294) and duplicated info. in Vol. 27 Pg. 11617)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground for ¼ cor. of sec. 32 only, with brass cap mkd. ¼S32
1918

from which

A Yellow Pine 24" dia., bears N.11°E., 81 lks. dist. mkd. ¼ S32 BT.

A B.Oak 16" dia., bears N.9°W., 53 lks. dist. mkd. ¼ S32 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Mike Darby and Terry Connell, crew - July 1965 - C.S. File 53/40-80

Found - 1918 GLO brass cap.

Orig. 16" now 16" B.Oak N.9°W., 35.0 ft., down and dead and rotted, shows "S32 B" scribe.

Orig. 24" now 36" Y.Pine N.11°E., 53.5 ft., shows scar, tree alive, we do not open.

New BT - 9" D.Fir N.46½°W., 11.8 ft. mkd. ¼ S32 CS BT.

This corner lies 162.4 ft. East of N. ¼ cor. of Sec. 5.

Fd. OK Sept. 1984 by H. Johnstone - M 97-50