

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5 of T32-7

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16, 1881 (DCSO records Vol. 19 Page(s) 8027)

 Set a Chinquapin post, 4½ ft. long, 4" sq., 20" in the ground for the cor. to secs. 4, 5, 32 and 33, marked T31S R7W S33 on NE. face; T32S S4 on SE. face; S5 on SW. face; S32 on NW. face; and also two notches on W. and four on E. angle of same, from which

- A Fir 14" dia., bears N.54°E., 17 lks. dist., mkd. T31S R7W S33 BT.
- A Fir 26" dia., bears S.36°E., 18 lks. dist., mkd. T32S R7W S4 BT.
- A Fir 16" dia., bears S.12°W., 60 lks. dist., mkd. T32S R7W S5 BT.
- A Laurel 8" dia., bears N.50°W., 9 lks. dist., mkd. T31S R7W S32 BT.

Cor. Fd. and Used in Byars GLO survey of 1882 (DCSO records, Vol. 21 Page 8751) AND (Vol. 19 Page 8062)

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531, surveyed Oct. 1963\June 1964 (DCSO records Vol. 33 Page(s) 13621)

 The Sec. cor., determined at record bearing and distance from the remaining original bearing trees:

- A Fir 18" dia., bears N.54°E., 17 lks. dist., mkd. S R7W on a bark blaze.
- A Fir 35" dia., bears S.36°E., 18 lks. dist., mkd. T32S R7W S4 BT on a bark blaze.
- A Fir 27" dia., bears S.12°W., 60 lks. dist., mkd. T32S R7W S5 BT on a bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked

| | |
|-------------|-------------|
| T 31 | S R 7 W |
| <u>S 32</u> | <u>S 33</u> |
| S 5 | S 4 |
| T 32 | S R 7 W |
| 1966 | |

from which new bearing trees

- A Fir 19" dia., bears N.79½°E., 88 lks. dist., mkd. T31S R7W S33 BT.
- A Fir 17" dia., bears N.54¼°W., 74 lks. dist., mkd. T31S R7W S32 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; and 4 & 5, T32-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1086, surveyed April/June 1982 (DCSO records Vol. 46 Page(s) 17550-51)

The Sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground with a 1964 brass cap, from which the remains of the original bearing trees:

A sawed Fir stump 34" dia., bears S.36°E., 18 lks. dist., with fragmentary scribe marks visible on bark blaze.

A Fir 28" dia., bears S.12°W., 60 lks. dist., with fragmentary scribe marks visible on bark blaze.

and the remains of bearing trees mkd. by Beck:

A Fir 21" dia., bears N.79½°E., 88 lks. dist., with healed blaze.

A sawed Fir stump 18" dia., bears N.54¼°W., 74 lks. dist., with healed blaze.

and new bearing trees:

A Fir 21" dia., bears S.40°E., 106 lks. dist., mkd. T32S R7W S4 BT.

A Cedar 8" dia., bears N.58°W., 83 lks. dist., mkd. T31S R7W S32 BT.

Survey by Kristian DeGroot, L.S. #1941 - For: Allen & Gibbons Logging - Nov. 28, 1983 - C.S. File 58/229-23

Found - 1964 BLM brass cap properly mkd. on a 2½" I.P. projecting 2" above ground.

Orig. BT, 34" D.Fir stump, bears S.36°E., 11.9 ft. with bark scribe marks "T32S 7W S4 BT" visible.

Orig. 26" D.Fir stump, bears S.12°W., 37.8 ft. with bark scribe marks "T32S R7W S5 BT" visible. (Rec. 39.8 ft.)

1964 BT, 19" D.Fir stump, bears N.79½°E., 58.1 ft. with healed blaze.

1964 BT, 18" D.Fir stump, bears N.54½°W., 48.8 ft. with healed blaze.

1982 BT, 20" D.Fir stump, bears S.40°E., 51.0 ft. with scribe marks "T32S R7W S4 BT" visible. (Rec. 52.8 ft. from BT tag)

1982 BT, 8" Cedar bears N.58°W., 54.8 ft. with scribe marks "T31S R7W S32 BT" visible.

New BT - 8" TanOak bears N.45½°E., 120.9 ft. scribed "T31S R7W S33 BT" with a brass washer stamped "LS 1941" nailed into lower blaze.

I painted 6" red bands around new BTs and all BT faces red and attached BT tags. Distance to new BT measured to a nail in root crown at the side and center of the tree.